

MASTER PL-L 24W/827/4P 1CT/25

Kod produktu: 57739



Dane techniczne:

- Color Code **827 [CCT of 2700K]**
- Color Temperature **2700 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **B**
- Diameter D **37.7 (max) mm**
- Overall Length C **321.6 (max) mm**
- Full product code **927903208270**
- Full product name **MASTER PL-L 24W/827/4P 1CT**
- Order code **927903208270**
- Order product name **MASTER PL-L 24W/827/4P 1CT/25**
- Packing configuration **25**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500710765**
- Bar code on pack - EAN1 **8711500706706**
- Packs per outerbox **25**
- Logistic code(s) - 12NC **927903208270**
- Net weight per piece **82.000 gr**
- Lamp Wattage **24 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSD-24/27/1B-E-2G11**
- Base **2G11**
- Base Information **4P**
- Mercury (Hg) Content **2.0 mg**
- Insertion Length B **315 (max) mm**
- Chromaticity Coordinate X **465 -**
- Chromaticity Coordinate Y **420 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **96 %**
- LSF EM 8000h Rated,3h cycle **94 %**
- LLMF EM 2000h Rated **94 %**
- LLMF EM 4000h Rated **93 %**
- LLMF EM 6000h Rated **92 %**
- LLMF EM 8000h Rated **91 %**
- Design Temperature **30 C**

- Lamp Wattage EM 25°C, Nominal **24 W**
- Lamp Current EM 25°C **0.345 A**
- Lamp Voltage EM 25°C **87 V**
- Lamp Wattage EM 25°C, Rated **24.0 W**
- Base Face to Base Face A **289.2 (max) mm**
- Diameter D1 **18 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **99 %**
- LSF HF Preheat 12000h Rated,3h **94 %**
- LSF HF Preheat 6000h Rated,3h **98 %**
- LSF HF Preheat 8000h Rated,3h **97 %**
- LSF HF Preheat 16000h Rated,3h **82 %**
- Luminous Flux EL 25°C, Nominal **1800 Lm**
- Luminous Flux EL 25°C, Rated **1800 Lm**
- LLMF HF 2000h Rated **95 %**
- LLMF HF 4000h Rated **94 %**
- LLMF HF 12000h Rated **91 %**
- LLMF HF 6000h Rated **93 %**
- LLMF HF 8000h Rated **92 %**
- Lamp Wattage EL 25°C, Rated **24.0 W**
- Lamp Voltage EL 25°C **75 V**
- Lamp Wattage EL 25°C, Nominal **24 W**
- Lamp Current EL 25°C **0.300 A**
- LSF HF Preheat 20000h Rated,3h **50 %**
- LSF EM 12000h Rated,3h cycle **80 %**
- LLMF EM 12000h Rated **90 %**
- LLMF HF 16000h Rated **90 %**
- LLMF HF 20000h Rated **90 %**
- Lum Efficacy Rated EM 25°C,hor **75 Lm/W**
- Lum Flux Nominal EM 25°C,horiz **1800 Lm**
- Lum Flux Rated EM 25°C,horiz **1800 Lm**
- Lum Flux Rated HF 25°C,horiz **1800 Lm**
- Lum Efficacy Rated HF 25°C,hor **75 Lm/W**
- Lum Flux Nominal HF 25°C,horiz **1800 Lm**
- Avg. Life **15000 hr**
- Color Designation **Incandescent White**

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Features

Available in multiple sizes

For use on Rapid Start, Instant Start (40W), Electronic and dimming circuits

Light output comparable to a 32W 4' fluorescent

90% lumen maintenance

82 CRI or higher

Available in 18, 24, 36, 40, 50, 55, and 80 watts with 3000, 3500, 4100, 5000 color temperatures (5000K color temperature is only available in 55W)

Just 1.4mg of mercury

Applications

perfect for 2' x 2' fixtures in office and healthcare facilities.

