

MASTER PL-T 18W/830/2P 1CT/5X10BOX

Kod produktu: 57764



Dane techniczne:

- Cap-Base **GX24d-2**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **22 kWh**
- Diameter D **41 (max) mm**
- Overall Length C **119.2 (max) mm**
- Full product code **927914383071**
- Full product name **MASTER PL-T 18W/830/2P 1CT**
- Order code **927914383071**
- Order product name **MASTER PL-T 18W/830/2P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500610591**
- Bar code on pack - EAN1 **8711500610508**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927914383071**
- Net weight per piece **59.000 gr**
- Bar code on intermediate packing - EAN2 **8711500610515**
- Cap-Base Information **2P**
- Lamp Wattage **18 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSM-18/30/1B-I-GX24d=2**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **96.0 (max) mm**
- Chromaticity Coordinate X **434 -**
- Chromaticity Coordinate Y **397 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **92 %**
- LSF EM 8000h Rated,3h cycle **78 %**
- LLMF EM 2000h Rated **92 %**
- Lum Efficacy Rated EM 25°C **67 (min) Lm/W**

- Luminous Flux EM 25°C, Nominal **1200 Lm**
- Luminous Flux EM 25°C, Rated **1200 Lm**
- LLMF EM 4000h Rated **87 %**
- LLMF EM 6000h Rated **84 %**
- LLMF EM 8000h Rated **81 %**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **18 W**
- Lamp Current EM 25°C **0.225 A**
- Lamp Voltage EM 25°C **100 V**
- Lamp Wattage EM 25°C, Rated **18.0 W**
- Base Face to Base Face A **71.8 (max) mm**

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Features

2-pin base with a housing incorporating the special instant starter and capacitor

Philips' bridging technology applied

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Fast light run-up

Applications

Designed for general or supplementary lighting in professional and semi-professional environments

Ideal for use in recessed or surface mounted downlighters, wall units



