

# MASTER PL-T 26W/830/4P 1CT/5X10BOX

Kod produktu: 57776



## Dane techniczne:

- Cap-Base **GX24q-3**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **29 kWh**
- Diameter D **41.0 (max) mm**
- Overall Length C **126.7 (max) mm**
- Full product code **927914683071**
- Full product name **MASTER PL-T 26W/830/4P 1CT**
- Order code **927914683071**
- Order product name **MASTER PL-T 26W/830/4P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500611246**
- Bar code on pack - EAN1 **8711500611208**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927914683071**
- Net weight per piece **64.000 gr**
- Bar code on intermediate packing - EAN2 **8711500272188**
- Cap-Base Information **4P**
- Lamp Wattage **26 W**
- Color Rendering Index **83 Ra8**
- ILCOS code **FSM-26/30/1B-E-GX24q=3**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **111.0 (max) mm**
- Chromaticity Coordinate X **434 -**
- Chromaticity Coordinate Y **397 -**
- Design Temperature **28 C**
- Base Face to Base Face A **86.7 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **60 %**
- LSF HF Preheat 6000h Rated,3h **97 %**

- LSF HF Preheat 8000h Rated, 3h **90 %**
- Luminous Flux EL 25°C, Nominal **1800 Lm**
- Luminous Flux EL 25°C, Rated **1725 Lm**
- LLMF HF 2000h Rated **92 %**
- LLMF HF 4000h Rated **88 %**
- LLMF HF 12000h Rated **81 %**
- LLMF HF 6000h Rated **86 %**
- LLMF HF 8000h Rated **84 %**
- Lamp Wattage EL 25°C, Rated **24.0 W**
- Lamp Voltage EL 25°C **80 V**
- Lamp Wattage EL 25°C, Nominal **26 W**
- Lamp Current EL 25°C **0.300 A**
- Lum Efficacy Rated HF 25°C **72 (min) Lm/W**

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

## Features

4-pin base

Philips' bridging technology applied

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Fast light run-up

## Applications

Designed for general or supplementary lighting in professional and semi-professional environments

Ideal for use in recessed or surface mounted downlighters, wall units, outdoor lighting

First choice for short switching cycles, emergency lighting and deep dimming



