

MASTER PL-T 42W/827/4P 1CT/5X10BOX

Kod produktu: 57780



Dane techniczne:

- Cap-Base **GX24q-4**
- Color Code **827 [CCT of 2700K]**
- Color Designation (text) **Incandescent White**
- Color Temperature **2700 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **45 kWh**
- Diameter D **41.0 (max) mm**
- Overall Length C **160.7 (max) mm**
- Full product code **927914882771**
- Full product name **MASTER PL-T 42W/827/4P 1CT**
- Order code **927914882771**
- Order product name **MASTER PL-T 42W/827/4P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500272195**
- Bar code on pack - EAN1 **8711500560025**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927914882771**
- Net weight per piece **83.000 gr**
- Bar code on intermediate packing - EAN2 **8711500560032**
- Cap-Base Information **4P**
- Lamp Wattage **42 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSMH-42/27/1B-L/P-GX24q=4**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **145.0 (max) mm**
- Chromaticity Coordinate X **455 -**
- Chromaticity Coordinate Y **417 -**
- Design Temperature **28 C**
- Base Face to Base Face A **120.7 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **60 %**
- LSF HF Preheat 6000h Rated,3h **97 %**

- LSF HF Preheat 8000h Rated, 3h **90 %**
- Luminous Flux EL 25°C, Nominal **3200 Lm**
- Luminous Flux EL 25°C, Rated **3050 Lm**
- LLMF HF 2000h Rated **92 %**
- LLMF HF 4000h Rated **88 %**
- LLMF HF 12000h Rated **81 %**
- LLMF HF 6000h Rated **86 %**
- LLMF HF 8000h Rated **84 %**
- Lamp Wattage EL 25°C, Rated **41.0 W**
- Lamp Voltage EL 25°C **125 V**
- Lamp Wattage EL 25°C, Nominal **42 W**
- Lamp Current EL 25°C **0.320 A**
- Lum Efficacy Rated HF 25°C **74 (min) Lm/W**
- Calibration Current **0.320 A**
- HF Generator Rated Voltage **270 V**
- Resistor **420 ohm**

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Features

4-pin base

Philips' bridging technology applied

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Fast light run-up

Applications

Designed for general or supplementary lighting in professional and semi-professional environments

Ideal for use in recessed or surface mounted downlighters, wall units, outdoor lighting

First choice for short switching cycles, emergency lighting and deep dimming



