

MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX

Kod produktu: 57792



Dane techniczne:

- Cap-Base **GX24q-3**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **36 kWh**
- Diameter D **41 (max) mm**
- Overall Length C **138.7 (max) mm**
- Full product code **927911984069**
- Full product name **MASTER PL-T TOP 32W/840/4P 1CT**
- Order code **927911984069**
- Order product name **MASTER PL-T TOP 32W/840/4P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500610034**
- Bar code on pack - EAN1 **8711500560261**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927911984069**
- Net weight per piece **70.000 gr**
- Bar code on intermediate packing - EAN2 **8711500560278**
- Cap-Base Information **4P**
- Lamp Wattage **32 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSMH-32/40/1B-L/P-GX24q=3**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **123.0 (max) mm**
- Chromaticity Coordinate X **380 -**
- Chromaticity Coordinate Y **379 -**
- Design Temperature **28 C**
- Base Face to Base Face A **98.7 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **60 %**
- LSF HF Preheat 6000h Rated,3h **97 %**

- LSF HF Preheat 8000h Rated, 3h **90 %**
- Luminous Flux EL 25°C, Nominal **2400 Lm**
- Luminous Flux EL 25°C, Rated **2400 Lm**
- LLMF HF 2000h Rated **92 %**
- LLMF HF 4000h Rated **88 %**
- LLMF HF 12000h Rated **81 %**
- LLMF HF 6000h Rated **85 %**
- LLMF HF 8000h Rated **84 %**
- Lamp Wattage EL 25°C, Rated **32.0 W**
- Lamp Voltage EL 25°C **105 V**
- Lamp Wattage EL 25°C, Nominal **32 W**
- Lamp Current EL 25°C **0.320 A**
- Lum Efficacy Rated HF 25°C **75 (min) Lm/W**
- Calibration Current **0.320 A**
- HF Generator Rated Voltage **200 V**
- Resistor **315 ohm**

MASTER PL-T TOP is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The Philips amalgam technology guarantees optimum performance in applications with a wide temperature range, enabling significantly higher output and efficacy levels. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-T TOP is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The Philips amalgam technology guarantees optimum performance in applications with a wide temperature range, enabling significantly higher output and efficacy levels. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Features

4-pin base

Philips amalgam technology applied

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Applications

Designed for general or supplementary lighting in professional and semi-professional environments

Ideal for use in recessed or surface mounted downlighters, wall units

First choice for long switching cycles and highest light output



