

MASTER PL-T Xtra 32W/840/4P 1CT/5X10BOX

Kod produktu: 57803



Dane techniczne:

- Cap-Base **GX24q-3**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **35 kWh**
- Diameter D **41.0 (max) mm**
- Overall Length C **138.7 (max) mm**
- Full product code **927912584014**
- Full product name **MASTER PL-T Xtra 32W/840/4P 1CT**
- Order code **927912584014**
- Order product name **MASTER PL-T Xtra 32W/840/4P 1CT/5X10BOX**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500897459**
- Bar code on pack - EAN1 **8711500897435**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927912584014**
- Net weight per piece **70.000 gr**
- Bar code on intermediate packing - EAN2 **8711500897442**
- Cap-Base Information **4P**
- Lamp Wattage **32 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSMH-32/40/1B-L/P-GX24q=3**
- Mercury (Hg) Content **3.0 mg**
- Insertion Length B **123.0 (max) mm**
- Chromaticity Coordinate X **380 -**
- Chromaticity Coordinate Y **379 -**
- Design Temperature **28 C**
- Base Face to Base Face A **98.7 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **95 %**
- LSF HF Preheat 6000h Rated,3h **97 %**

- LSF HF Preheat 8000h Rated, 3h **96 %**
- LSF HF Preheat 16000h Rated, 3h **94 %**
- Luminous Flux EL 25°C, Nominal **2300 Lm**
- Luminous Flux EL 25°C, Rated **2400 Lm**
- LLMF HF 2000h Rated **92 %**
- LLMF HF 4000h Rated **88 %**
- LLMF HF 12000h Rated **81 %**
- LLMF HF 6000h Rated **86 %**
- LLMF HF 8000h Rated **84 %**
- Lamp Wattage EL 25°C, Rated **32.0 W**
- Lamp Voltage EL 25°C **101 V**
- Lamp Wattage EL 25°C, Nominal **32 W**
- Lamp Current EL 25°C **0.320 A**
- Lum Efficacy Rated HF 25°C **75 Lm/W**
- LSF HF Preheat 20000h Rated, 3h **90 %**
- LLMF HF 16000h Rated **79 %**
- LLMF HF 20000h Rated **78 %**
- Calibration Current **0.320 A**
- HF Generator Rated Voltage **200 V**
- Resistor **315 ohm**

MASTER PL-T Xtra is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. MASTER PL-T Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-T lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-T Xtra is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. MASTER PL-T Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-T lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Features

4-pin base
Philips bridging technology applied
Extra long lifetime and less early failures
Fluorescent tri-phosphor technology
Low light depreciation over lamp life
Fast light run-up

Applications

Designed for general or supplementary lighting in professional and semi-professional environments
Ideal for use in recessed or surface mounted downlighters, wall units, outdoor lighting
Suitable for use in applications where maintenance costs are high (high ceilings, difficult to reach): department stores, supermarkets, warehouses, production halls and public areas

