

# MASTER TL-D Super 80 30W/830 1SL/25

Kod produktu: 57838



## Dane techniczne:

- Cap-Base **G13 [Medium Bi-Pin Fluorescent]**
- Bulb **T8 [26 mm]**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **36 kWh**
- Diameter D **28 (max) mm**
- Overall Length C **908.8 (max) mm**
- Full product code **927920583023**
- Full product name **MASTER TL-D Super 80 30W/830 1SL**
- Order code **927920583023**
- Order product name **MASTER TL-D Super 80 30W/830 1SL/25**
- Packing configuration **25**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500631848**
- Bar code on pack - EAN1 **8711500631831**
- Packs per outerbox **25**
- Logistic code(s) - 12NC **927920583023**
- Net weight per piece **103.600 gr**
- Cap-Base Information **Green Plate**
- Lamp Wattage **30 W**
- Color Rendering Index **85 Ra8**
- ILCOS code **FD-30/30/1B-E-G13**
- Mercury (Hg) Content **2.0 mg**
- Insertion Length B **899.3 (min), 901.7 (max) mm**
- Chromaticity Coordinate X **440 -**
- Chromaticity Coordinate Y **403 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **99 %**
- LSF EM 6000h Rated,3h cycle **99 %**
- LSF EM 8000h Rated,3h cycle **99 %**
- LLMF EM 2000h Rated **96 %**
- Lum Efficacy Rated EM 25°C **80 Lm/W**
- Luminous Flux EM 25°C, Nominal **2400 Lm**
- Luminous Flux EM 25°C, Rated **2400 Lm**
- LLMF EM 4000h Rated **95 %**
- LLMF EM 6000h Rated **94 %**
- LLMF EM 8000h Rated **93 %**

- Design Temperature **25 °C**
- Lamp Wattage EM 25 °C, Nominal **30 W**
- Lamp Current EM 25 °C **0.360 A**
- Lamp Voltage EM 25 °C **98 V**
- Lamp Wattage EM 25 °C, Rated **30.0 W**
- Base Face to Base Face A **894.6 (max) mm**
- LSF EM 12000h Rated, 3h cycle **89 %**
- LSF EM 16000h Rated, 3h cycle **33 %**
- LLMF EM 12000h Rated **92 %**
- LLMF EM 16000h Rated **91 %**
- LLMF EM 20000h Rated **90 %**
- LSF EM 20000h Rated, 3h cycle **2 %**
- Luminance Average EM **1.10 cd/cm<sup>2</sup>**

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

### Features

Highly efficient 3-band fluorescent coating  
High initial light output compared with standard colors  
Low mercury dose  
Can be used with conventional or electronic gear  
Higher efficacy is achieved with electronic gear

### Applications

Suitable for use in a wide range of luminaires for TL-D fluorescent lamps for 'human' applications such as schools, offices, shops, factory halls etc.



