

MASTER TL-D Eco 16W/830 SLV/25

Kod produktu: 57852



Dane techniczne:

- Cap-Base **G13 [Medium Bi-Pin Fluorescent]**
- Bulb **T8 [26 mm]**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **19 kWh**
- Diameter D **28 (max) mm**
- Overall Length C **604.0 (max) mm**
- Full product code **927922883015**
- Full product name **MASTER TL-D Eco 16W/830 1SL**
- Order code **927922883015**
- Order product name **MASTER TL-D Eco 16W/830 1SL/25**
- Packing configuration **25**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500268587**
- Bar code on pack - EAN1 **8711500268570**
- Packs per outerbox **25**
- Logistic code(s) - 12NC **927922883015**
- Net weight per piece **68.900 gr**
- Lamp Wattage **16 W**
- Color Rendering Index **85 Ra8**
- ILCOS code **FD-16/30/1B-E-G13-26/604**
- Mercury (Hg) Content **2.0 mg**
- Insertion Length B **594.5 (min), 596.9 (max) mm**
- Chromaticity Coordinate X **438 -**
- Chromaticity Coordinate Y **404 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **99 %**
- LSF EM 6000h Rated,3h cycle **99 %**
- LSF EM 8000h Rated,3h cycle **99 %**
- LLMF EM 2000h Rated **96 %**
- Lum Efficacy Rated EM 25°C **75 Lm/W**
- Luminous Flux EM 25°C, Nominal **1175 Lm**
- Luminous Flux EM 25°C, Rated **1175 Lm**
- LLMF EM 4000h Rated **95 %**
- LLMF EM 6000h Rated **94 %**
- LLMF EM 8000h Rated **93 %**
- Design Temperature **30 C**
- Lamp Wattage EM 25°C, Nominal **16 W**
- Lamp Current EM 25°C **0.380 A**

- Lamp Voltage EM 25°C **51 V**
- Lamp Wattage EM 25°C, Rated **15.7 W**
- Base Face to Base Face A **589.8 (max) mm**
- LSF EM 12000h Rated,3h cycle **89 %**
- LSF EM 16000h Rated,3h cycle **33 %**
- LLMF EM 12000h Rated **92 %**
- LLMF EM 16000h Rated **91 %**
- LLMF EM 20000h Rated **90 %**
- LSF EM 20000h Rated,3h cycle **2 %**
- Luminous Flux Lamp EM 30°C **1300 Lm**

The MASTER TL-D Eco lamp offers the same light output as a MASTER TL-D Super 80 lamp, while using less energy, thanks to the use of specific phosphors and a special gas filling. Application areas are schools, offices, governmental buildings and healthcare environments.

The MASTER TL-D Eco lamp offers the same light output as a MASTER TL-D Super 80 lamp, while using less energy, thanks to the use of specific phosphors and a special gas filling. Application areas are schools, offices, governmental buildings and healthcare environments.

Features

The only T8 fluorescent lamp that saves more than 10% of energy in existing luminaires with electromagnetic gear
Lower power savings with electronic gear depending on type of gear (current- or power-controlled)

Can be directly retrofitted into existing fluorescent fittings operating on electromagnetic or electronic gear in indoor applications

Uses the latest highly efficient phosphors and special filling gas

High-quality lighting with good color rendering (CRI>80)

Light output comparable to other TL-D Super 80 colors

Lumen maintenance and lifetime the same as other TL-D Super 80 colors

Dimmable

Applications

For use in indoor applications with room temperatures above 20 °C (which implies temperature around the lamp of over 25-35 °C)

Primary focus on offices, schools and hospitals; secondary focus on retail, industry, supermarkets

Not recommended under the following conditions:- with air flow around the lamps- in luminaires with active air handling (lamp temperature will not be the required 25-35 °C, but roomtemperature)- in open luminaires/battens very close to air conditioning outlets or cold air flows- in space above freezers (temperature may easily drop below 20 °C)- in combination with VRUs (voltage reduction units)



