

MASTER TL-D 90 Graphica 18W/950 SLV/10

Kod produktu: 57880



Dane techniczne:

- Cap-Base **G13 [Medium Bi-Pin Fluorescent]**
- Bulb **T8 [26 mm]**
- Color Code **950 [CCT of 5000K]**
- Color Designation (text) **Daylight**
- Color Temperature **5300 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **22 kWh**
- Diameter D **28 (max) mm**
- Overall Length C **604 (max) mm**
- Full product code **928043795081**
- Full product name **MASTER TL-D 90 Graphica 18W/950 1SL**
- Order code **928043795081**
- Order product name **MASTER TL-D 90 Graphica 18W/950 1SL/10**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500888518**
- Bar code on pack - EAN1 **8711500888501**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **928043795081**
- Net weight per piece **38.200 gr**
- Lamp Wattage **18 W**
- Color Rendering Index **97 Ra8**
- ILCOS code **FD-18/53/1A-E-G13**
- Mercury (Hg) Content **3.0 mg**
- Insertion Length B **594.5 (min), 596.9 (max) mm**
- Chromaticity Coordinate X **342 -**
- Chromaticity Coordinate Y **352 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **99 %**
- LSF EM 6000h Rated,3h cycle **99 %**
- LSF EM 8000h Rated,3h cycle **99 %**
- LLMF EM 2000h Rated **93 %**
- Lum Efficacy Rated EM 25°C **52.8 Lm/W**
- Luminous Flux EM 25°C, Nominal **950 Lm**
- Luminous Flux EM 25°C, Rated **950 Lm**
- LLMF EM 4000h Rated **90 %**
- LLMF EM 6000h Rated **88 %**
- LLMF EM 8000h Rated **85 %**
- Design Temperature **25 C**

- Lamp Wattage EM 25°C, Nominal **18 W**
- Lamp Current EM 25°C **0.360 A**
- Lamp Voltage EM 25°C **59 V**
- Lamp Wattage EM 25°C, Rated **18.0 W**
- Base Face to Base Face A **589.8 (max) mm**
- LSF EM 12000h Rated,3h cycle **89 %**
- LSF EM 16000h Rated,3h cycle **33 %**
- LLMF EM 12000h Rated **82 %**
- LLMF EM 16000h Rated **80 %**
- LLMF EM 20000h Rated **78 %**
- LSF EM 20000h Rated,3h cycle **2 %**
- Luminance Average EM **0.80 cd/cm²**

This TL-D lamp has excellent color rendering which makes it very suitable for the graphical and printing industry to check the quality of printed material.

This TL-D lamp has excellent color rendering which makes it very suitable for the graphical and printing industry to check the quality of printed material.

Features

High-quality fluorescent coating for excellent color rendering and very accurate color point

Use of mix of three-band phosphors and halophosphates for high efficacy

Retrofit in current luminaires for standard TL-D lamps

Applications

Used in applications where excellent color rendering is crucial, such as the graphical industry, printing industry, photo shops, hospitals, etc.



