

TL-E 32W/830 1CT/12

Kod produktu: 57946



Dane techniczne:

- Cap-Base **G10q**
- Bulb **C-T9 [C-T 29 mm]**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **35 kWh**
- Diameter D **27.1 (min), 30.9 (max) mm**
- Full product code **928026383074**
- Full product name **MASTER TL-E Circular Super 80 32W/830 1CT**
- Order code **928026383074**
- Order product name **MASTER TL-E Circular 32W/830 1CT/20**
- Packing configuration **20**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900813593**
- Bar code on pack - EAN1 **8711500559678**
- Packs per outerbox **20**
- Logistic code(s) - 12NC **928026383074**
- Net weight per piece **0.180 kg**
- Lamp Wattage **32 W**
- Overall Width E **299.0 (min), 303.5 (max) mm**
- Color Rendering Index **85 Ra8**
- ILCOS code **FSC-32/30/1B-E-G10q-29/299**
- Mercury (Hg) Content **8 mg**
- Chromaticity Coordinate X **438 -**
- Chromaticity Coordinate Y **403 -**
- LSF EM 2000h Rated,3h cycle **98 %**
- LSF EM 4000h Rated,3h cycle **77 %**
- LSF EM 6000h Rated,3h cycle **60 %**
- LSF EM 8000h Rated,3h cycle **45 %**
- LLMF EM 2000h Rated **90 %**
- Lum Efficacy Rated EM 25°C **74 Lm/W**
- Luminous Flux EM 25°C, Nominal **2375 Lm**
- Luminous Flux EM 25°C, Rated **2375 Lm**

- LLMF EM 4000h Rated **87 %**
- LLMF EM 6000h Rated **85 %**
- LLMF EM 8000h Rated **84 %**
- Design Temperature **25 C**
- Lamp Wattage EM 25°C, Nominal **32 W**
- Lamp Current EM 25°C **0.450 A**
- Lamp Voltage EM 25°C **81 V**
- Lamp Wattage EM 25°C, Rated **32.0 W**
- Luminance Average EM **0.85 cd/cm2**
- Inner Width I **241.0 (min), 246.0 (max) mm**

This circular TL lamp (tube diameter 29 mm) enables omni-directional light distribution. It is suitable for use in a wide range of luminaires for various purposes, including decorative ones, in 'human' applications such as schools, offices, shops and homes, and for lighting of residential areas.

This circular TL lamp (tube diameter 29 mm) enables omni-directional light distribution. It is suitable for use in a wide range of luminaires for various purposes, including decorative ones, in 'human' applications such as schools, offices, shops and homes, and for lighting of residential areas.

Features

Available in various color designations

Applications

Suitable for use in a wide range of luminaires for various purposes, including decorative luminaires

Ideal for 'human' applications such as schools, offices, shops and homes

