

MASTER TL5 HE 28W/865 SLV/40

Kod produktu: 57978



Dane techniczne:

- Bulb **T5 [16 mm]**
- Color Code **865 [CCT of 6500K]**
- Color Temperature **6500 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Diameter D **17 (max) mm**
- Overall Length C **1163.2 (max) mm**
- Full product code **927926586555**
- Full product name **MASTER TL5 HE 28W/865 1SL**
- Order code **927926586555**
- Order product name **MASTER TL5 HE 28W/865 1SL/40**
- Packing configuration **40**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500867612**
- Bar code on pack - EAN1 **8711500710154**
- Packs per outerbox **40**
- Logistic code(s) - 12NC **927926586555**
- Net weight per piece **83.000 gr**
- System Description **High Efficiency**
- Lamp Wattage **28 W**
- Color Rendering Index **85 Ra8**
- ILCOS code **FDH-28/65/1B-L/P-G5-16/1150**
- Base **Miniature Bipin**
- Base Information **Green Plate**
- Mercury (Hg) Content **1.4 mg**
- Initial Lumens **2700 Lm**
- Insertion Length B **1153.7 (min), 1156.1 (max) mm**
- Chromaticity Coordinate X **313 -**
- Chromaticity Coordinate Y **338 -**
- Design Temperature **35 C**
- Base Face to Base Face A **1149.0 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **95 %**
- LSF HF Preheat 6000h Rated,3h **98 %**
- LSF HF Preheat 8000h Rated,3h **97 %**
- LSF HF Preheat 16000h Rated,3h **94 %**
- Luminous Flux EL 25°C, Nominal **2400 Lm**
- Luminous Flux EL 25°C, Rated **2400 Lm**
- LLMF HF 2000h Rated **96 %**

- LLMF HF 4000h Rated **95 %**
- LLMF HF 12000h Rated **91 %**
- LLMF HF 6000h Rated **94 %**
- LLMF HF 8000h Rated **93 %**
- Lamp Wattage EL 25°C, Rated **28.2 W**
- Lamp Voltage EL 25°C **166 V**
- Lamp Wattage EL 25°C, Nominal **28 W**
- Lamp Current EL 25°C **0.170 A**
- Lum Efficacy Rated HF 25°C **85 Lm/W**
- LSF HF Preheat 20000h Rated,3h **85 %**
- LLMF HF 16000h Rated **90 %**
- LLMF HF 20000h Rated **88 %**
- Color Designation **Cool Daylight**
- Calibration Current **0.170 A**
- HF Generator Rated Voltage **329 V**
- Resistor **950 ohm**
- Lum Efficacy Rated HF 35°C **97 Lm/W**
- Lamp Voltage EL 35°C **167 V**
- Lamp Wattage EL 35°C **27.8 W**
- Lamp Current EL 35°C **0.170 A**
- Luminance Average EL 25°C **1.4 cd/cm2**

Philips T5 Fluorescent Lamps featuring ALTO® Lamp Technology offer increased energy savings and low toxicity in a slim profile

Philips T5 Fluorescent Lamps featuring ALTO® Lamp Technology offer increased energy savings and low toxicity in a slim profile.

Features

Less mercury combined with energy efficiency and long life reduces the impact on the environment.

Our green end-caps mean you are using ALTO® environmentally-responsible lamps.

Only 1.4mg of mercury per lamp.

Slim profile lamp and ballast.

Operates on programmed start electronic ballasts only.

Available in 14, 21, 28, and 35 Watts with 3000, 3500, 4100 color temperatures.

Applications

Ideal for general, decorative and architectural lighting in offices, retail stores, hotels, schools and hospitals.



