

MASTER TL5 HO 54W/840 SLV/40

Kod produktu: 57999



Dane techniczne:

- Bulb **T5 [16 mm]**
- Color Code **841 [CCT of 4100K]**
- Color Temperature **4100 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Diameter D **17 (max) mm**
- Overall Length C **1163.2 (max) mm**
- Full product code **927929084055**
- Full product name **MASTER TL5 HO 54W/840 1SL**
- Order code **927929084055**
- Order product name **MASTER TL5 HO 54W/840 1SL/40**
- Packing configuration **40**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500868831**
- Bar code on pack - EAN1 **8711500643186**
- Packs per outerbox **40**
- Logistic code(s) - 12NC **927929084055**
- Net weight per piece **104.500 gr**
- System Description **High Output**
- Lamp Wattage **54 W**
- Color Rendering Index **85 Ra8**
- ILCOS code **FDH-54/40/1B-L/P-G5-16/1150**
- Base **Miniature Bipin**
- Base Information **Green Plate**
- Mercury (Hg) Content **1.4 mg**
- Initial Lumens **5000 Lm**
- Insertion Length B **1153.7 (min), 1156.1 (max) mm**
- Chromaticity Coordinate X **383 -**
- Chromaticity Coordinate Y **386 -**
- Design Temperature **35 C**
- Base Face to Base Face A **1149.0 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **95 %**
- LSF HF Preheat 6000h Rated,3h **98 %**
- LSF HF Preheat 8000h Rated,3h **97 %**
- LSF HF Preheat 16000h Rated,3h **94 %**
- Luminous Flux EL 25°C, Nominal **4450 Lm**
- Luminous Flux EL 25°C, Rated **4450 Lm**
- LLMF HF 2000h Rated **96 %**

- LLMF HF 4000h Rated **95 %**
- LLMF HF 12000h Rated **91 %**
- LLMF HF 6000h Rated **94 %**
- LLMF HF 8000h Rated **93 %**
- Lamp Wattage EL 25°C, Rated **54.3 W**
- Lamp Voltage EL 25°C **118 V**
- Lamp Wattage EL 25°C, Nominal **54 W**
- Lamp Current EL 25°C **0.460 A**
- Lum Efficacy Rated HF 25°C **82 Lm/W**
- LSF HF Preheat 20000h Rated,3h **85 %**
- LLMF HF 16000h Rated **90 %**
- LLMF HF 20000h Rated **88 %**
- Color Designation **Cool White**
- Calibration Current **0.460 A**
- HF Generator Rated Voltage **235 V**
- Resistor **255 ohm**
- Lum Efficacy Rated HF 35°C **93 Lm/W**
- Lamp Voltage EL 35°C **118 V**
- Lamp Wattage EL 35°C **53.8 W**
- Lamp Current EL 35°C **0.460 A**
- Luminance Average EL 25°C **2.6 cd/cm2**

Philips T5 HO lamps are environmentally-responsible, ultra-slim and have extraordinary light output and longer life.

Philips T5 HO lamps are environmentally-responsible, ultra-slim and have extraordinary light output and longer life.

Features

Reduced maintenance and disposal costs.

Long life for an extended relamping cycle.

35,000 hours rated average life*.

Up to 70% more lumens than standard Standard T5 lamps.

95% lumen maintenance.

Reduces the impact on the environment: low mercury, energy efficiency, long life, and less material.

Only 1.4 mg of mercury, the lowest in the industry.

With just 12 Picograms per lumen hour†, these lamps allow for more design freedom and help exceed all LEED requirements◇.

24, 39, 54 and 80 Watt with 3000, 3500, 4100, 5000, and 6500 Color Temperatures.

Applications

Ideal for medium-bay and high-bay retail and industrial applications.

