

MASTER TL5 Circular 55W/840 1CT/10

Kod produktu: 58023



Dane techniczne:

- Cap-Base **2GX13**
- Bulb **C-T5 [C-T 16 mm]**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **61 kWh**
- Diameter D **14 (min), 18 (max) mm**
- Full product code **927965784013**
- Full product name **MASTER TL5 Circular 55W/840 1CT**
- Order code **927965784013**
- Order product name **MASTER TL5 Circular 55W/840 1CT/10**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500642523**
- Bar code on pack - EAN1 **8711500642516**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **927965784013**
- Net weight per piece **77.000 gr**
- Lamp Wattage **55 W**
- Overall Width E **293 (min), 305 (max) mm**
- Color Rendering Index **80 (min), 85 (nom), 85 (max) Ra8**
- ILCOS code **FSCH-55/40/1B-L/P-2GX13-16**
- Mercury (Hg) Content **2.5 mg**
- Chromaticity Coordinate X **380 -**
- Chromaticity Coordinate Y **380 -**
- Design Temperature **35 C**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **99 %**
- LSF HF Preheat 12000h Rated,3h **50 %**
- LSF HF Preheat 6000h Rated,3h **96 %**
- LSF HF Preheat 8000h Rated,3h **89 %**
- LSF HF Preheat 16000h Rated,3h **10 %**
- Luminous Flux EL 25°C, Nominal **4200 Lm**

- Luminous Flux EL 25°C, Rated **4200 Lm**
- LLMF HF 2000h Rated **91 %**
- LLMF HF 4000h Rated **87 %**
- LLMF HF 12000h Rated **77 %**
- LLMF HF 6000h Rated **84 %**
- LLMF HF 8000h Rated **81 %**
- Lamp Wattage EL 25°C, Rated **55.0 W**
- Lamp Voltage EL 25°C **101 V**
- Lamp Wattage EL 25°C, Nominal **55 W**
- Lamp Current EL 25°C **0.550 A**
- Lum Efficacy Rated HF 25°C **76 Lm/W**
- LSF HF Preheat 20000h Rated,3h **1 %**
- LLMF HF 16000h Rated **74 %**
- LLMF HF 20000h Rated **72 %**
- Calibration Current **0.550 A**
- HF Generator Rated Voltage **202 V**
- Resistor **185 ohm**
- Inner Width I **260 (min), 272 (max) mm**

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omni-directional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omni-directional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Features

Perfect circular shape

Highly efficient 3-band fluorescent coating

Specifically designed for operation with electronic gear

Can be ignited from -15 to +50 °C

Amalgam technology

Applications

Brings the benefits of TL5 lighting to an even wider range of attractive applications

Suitable for a wide range of professional and semi-professional applications

Ideal for use in shops, offices and public areas with non-traditional lay-outs

Amalgam lamps are limited suitable for dimming applications



