

MASTER SDW-T 35W/825 PG12-1 1SL/12

Kod produktu: 58047



Dane techniczne:

- Cap-Base **PG12-1**
- Bulb **T31 [T 31mm]**
- Color Code **825 [CCT of 2500K]**
- Color Designation (text) **Golden White**
- Color Temperature **2500 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **36 kWh**
- Diameter D **32 (max) mm**
- Overall Length C **149 (max) mm**
- Full product code **928153809230**
- Full product name **MASTER SDW-T 35W/825 PG12-1 1SL**
- Order code **928153809230**
- Order product name **MASTER SDW-T 35W/825 PG12-1 1SL/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500183125**
- Bar code on pack - EAN1 **8711500734020**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928153809230**
- Net weight per piece **0.048 kg**
- Bulb Finish **Clear**
- System Description **High Voltage [200-250V]**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **83 Ra8**
- ILCOS code **STH-35-H/E-PG12**
- Cap-Base Temperature **120 (max) C**
- Bulb Material **Soft Glass**
- Bulb Temperature **350 (max) C**
- Life to 50% failures **15000 hr**
- Color Temperature Technical **2500 K**
- Light Center Length L **91 mm**
- Mercury (Hg) Content **3.8 mg**
- Lumen Maintenance 2000h **95 %**

- Chromaticity Coordinate X **479 -**
- Chromaticity Coordinate Y **417 -**
- Lumen Maintenance 5000h **90 %**
- Lamp Wattage EM 25°C, Nominal **35.0 W**
- Lamp Wattage EM 25°C, Rated **33.0 W**
- Luminous Efficacy Lamp EM **40 Lm/W**
- Luminous Flux Lamp EM **1300 Lm**
- Lamp Voltage **96 V**
- Lamp Current EM **0.48 A**
- Luminance Average EM **300 cd/cm²**
- Life to 20% failures **12000 hr**
- Life to 5% failures **8000 hr**
- Useful Life **10000 hr**
- Arc Length ϕ **13 mm**

Range of high-efficiency, discharge lamps with warm color to be used in open luminaires





