

MST SDW-TG Mini 100W/825 GX12-1 1CT/12

Kod produktu: 58048



Dane techniczne:

- Cap-Base **GX12-1**
- Bulb **T19 [T 19mm]**
- Color Code **825 [CCT of 2500K]**
- Color Designation (text) **Golden White**
- Color Temperature **2500 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **110 kWh**
- Diameter D **20 (max) mm**
- Overall Length C **110 (max) mm**
- Full product code **928158905131**
- Full product name **MASTER SDW-TG Mini 100W/825 GX12-1 1CT**
- Order code **928158905131**
- Order product name **MST SDW-TG Mini 100W/825 GX12-1 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500202345**
- Bar code on pack - EAN1 **8711500202338**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928158905131**
- Net weight per piece **0.030 kg**
- Bulb Finish **Clear**
- Lamp Wattage **100 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **80 (min), 83 (nom) Ra8**
- ILCOS code **STH-100/25/1B-GX12-1**
- Cap-Base Temperature **280 (max) C**
- Bulb Temperature **650 (max) C**
- Pinch Temperature **350 (max) C**
- Life to 50% failures **10000 hr**
- Color Temperature Technical **2500 K**
- Light Center Length L **54.5 (min), 56 (nom), 57.5 (max) mm**
- Mercury (Hg) Content **13 mg**
- Lumen Maintenance 2000h **95 %**
- Chromaticity Coordinate X **469 -**

- Chromaticity Coordinate Y **406 -**
- Lumen Maintenance 5000h **80 %**
- Lamp Wattage EL 25°C, Rated **99.0 W**
- Lamp Wattage EL 25°C, Nominal **100.0 W**
- Lamp Voltage **91 V**
- Lumen Maintenance 10000h **75 %**
- Life to 20% failures **8000 hr**
- Life to 5% failures **5000 hr**
- Arc Length O **18 mm**
- Luminous Efficacy Lamp EL **50 Lm/W**
- Luminous Flux Lamp EL **4900 Lm**
- System Power EL **112 W**
- Ignition Time **60 (max) s**
- Lamp Current EL **1.1 A**
- Re-ignition Time [min] **1.5 (max) min**
- Run-up time 90% **2 (max) min**
- Reference Length A **96 (max) mm**
- Diameter D [inch] **0.75 in**
- Light Center Length L [inch] **4.2 in**
- Overall Length C [inch] **12.84375 (max) in**

Range of high-efficiency, discharge lamps with warm color to be used in small, open luminaires designed around MASTERColour CDM-T lamps

Range of high-efficiency, discharge lamps with warm color to be used in small, open luminaires designed around MASTERColour CDM-T lamps

Features

Unique warm color quality

Lamp design is well-suited to be used in luminaires for MASTERColour CDM-T power-spots

UV-block glass

Applications

Shop lighting (creates cosy atmosphere e.g. in furniture shops), excellent display of fresh goods (at butchers, bakeries, flower-shops)





