

SON 70W/220 I E27 1CT/24

Kod produktu: 58056



Dane techniczne:

- Cap-Base **E27**
- Bulb **B70 [B 70mm]**
- Color Code **220 [CCT of 2000K]**
- Color Temperature **2000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **77 kWh**
- Diameter D **71 (max) mm**
- Overall Length C **155 (max) mm**
- Full product code **928150108828**
- Full product name **SON 70W/220 I E27 1CT**
- Order code **928150108828**
- Order product name **SON 70W/220 I E27 1CT/24**
- Packing configuration **24**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500181879**
- Bar code on pack - EAN1 **8711500181862**
- Packs per outerbox **24**
- Logistic code(s) - 12NC **928150108828**
- Net weight per piece **0.057 kg**
- Bulb Finish **Coated**
- System Description **Internal Ignitor**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **25 (max) Ra8**
- ILCOS code **SE-70-H/I-E27**
- Cap-Base Temperature **200 (max) C**
- Bulb Temperature **350 (max) C**
- Life to 50% failures **28000 hr**
- Light Center Length L **105 mm**
- Mercury (Hg) Content **16.3 mg**
- Lumen Maintenance 2000h **88 %**
- Chromaticity Coordinate X **540 -**
- Chromaticity Coordinate Y **415 -**
- Lumen Maintenance 5000h **83.5 %**

- LLMF EM 2000h Rated **88 %**
- Lum Efficacy Rated EM 25°C **80 Lm/W**
- Luminous Flux EM 25°C, Rated **5600 Lm**
- LLMF EM 4000h Rated **84 %**
- LLMF EM 6000h Rated **83 %**
- LLMF EM 8000h Rated **81 %**
- Lamp Wattage EM 25°C, Nominal **70.0 W**
- Lamp Wattage EM 25°C, Rated **70.0 W**
- LLMF EM 12000h Rated **80 %**
- LLMF EM 16000h Rated **79 %**
- LLMF EM 20000h Rated **78 %**
- Luminous Efficacy Lamp EM **80 Lm/W**
- Luminous Flux Lamp EM **5600 Lm**
- Lamp Voltage **90 V**
- Lamp Current EM **0.98 A**
- Lumen Maintenance 10000h **81 %**
- Life to 20% failures **18000 hr**
- Life to 5% failures **10000 hr**
- LSF EM 2000h Rated, 12h cycle **99 %**
- LSF EM 4000h Rated, 12h cycle **99 %**
- LSF EM 6000h Rated, 12h cycle **98 %**
- LSF EM 8000h Rated, 12h cycle **97 %**
- LSF EM 12000h Rated, 12h cycle **92 %**
- LSF EM 16000h Rated, 12h cycle **84 %**
- LSF EM 20000h Rated, 12h cycle **74 %**
- Life to 10% failures **13000 hr**
- Lumen Maintenance 20000h **78 %**

High Pressure Sodium lamp with opalized ovoid outer bulb





