

# MST SON-T APIA Plus Xtra 70W E27 1SL/12

Kod produktu: 58068



## Dane techniczne:

- Cap-Base **E27**
- Bulb **T35 [T 35mm]**
- Color Temperature **1950 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **83 kWh**
- Diameter D **36 (max) mm**
- Overall Length C **156 (max) mm**
- Full product code **928150119227**
- Full product name **MASTER SON-T APIA Plus Xtra 70W E27 1SL**
- Order code **928150119227**
- Order product name **MST SON-T APIA Plus Xtra 70W E27 1SL/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900922912**
- Bar code on pack - EAN1 **8727900922905**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928150119227**
- Net weight per piece **0.046 kg**
- Bulb Finish **Clear**
- System Description **External Ignitor**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **25 (max) Ra8**
- ILCOS code **ST-70-H/E-E27**
- Cap-Base Temperature **200 (max) C**
- Bulb Temperature **350 (max) C**
- Life to 50% failures **40000 hr**
- Color Temperature Technical **1900 K**
- Light Center Length L **102 mm**
- Mercury (Hg) Content **12.0 mg**
- Chromaticity Coordinate X **540 -**
- Chromaticity Coordinate Y **420 -**
- LLMF EM 2000h Rated **92 %**
- Lum Efficacy Rated EM 25°C **97 Lm/W**

- Luminous Flux EM 25°C, Rated **7300 Lm**
- LLMF EM 4000h Rated **90 %**
- LLMF EM 6000h Rated **89 %**
- LLMF EM 8000h Rated **88 %**
- Lamp Wattage EM 25°C, Nominal **70.0 W**
- Lamp Wattage EM 25°C, Rated **75.0 W**
- LLMF EM 12000h Rated **87 %**
- LLMF EM 16000h Rated **86 %**
- LLMF EM 20000h Rated **86 %**
- Lamp Voltage **90 V**
- Lamp Current EM **0.975 A**
- Luminance Average EM **310 cd/cm2**
- Life to 20% failures **32000 hr**
- Life to 5% failures **24000 hr**
- Arc Length O **42 mm**
- Ignition Time **5 (max) s**
- Run-up time 90% **4 (max) min**
- LSF EM 2000h Rated, 12h cycle **99 %**
- LSF EM 4000h Rated, 12h cycle **99 %**
- LSF EM 6000h Rated, 12h cycle **99 %**
- LSF EM 8000h Rated, 12h cycle **99 %**
- LSF EM 12000h Rated, 12h cycle **99 %**
- LSF EM 16000h Rated, 12h cycle **99 %**
- LSF EM 20000h Rated, 12h cycle **97 %**
- Re-ignition Time [sec] **30 (max) s**
- Life to 10% failures **28000 hr**
- Ratio scotopic/photopic lumens **0.50 -**

High Pressure Sodium lamp with clear tubular outer bulb shape, high output and longest reliable lifetime

High Pressure Sodium lamp with clear tubular outer bulb shape, high output and longest reliable lifetime

## Features

Tubular outer bulb

Ceramic discharge tube with new Active Philips Integrated Antenna (APIA) for an improved and prolonged long and reliable lifetime up to 6 Years Service Lifetime (Xtra)

Robust construction with few welding points is highly vibration- and shock-resistant, further reducing early failures and extending lamp life

"Plus" concept with high efficacy translated into high light output

Completely lead-free lamps

## Applications

Road and residential lighting

Decorative floodlighting, illumination

Industrial area lighting

Recreational sports facilities indoor and outdoor



