

MST SON-T PIA Plus 50W/220 E27 1SL/12

Kod produktu: 58078



Dane techniczne:

- Cap-Base **E27**
- Bulb **T35 [T 35mm]**
- Color Code **220 [CCT of 2000K]**
- Color Temperature **2000 K**
- Voltage **230 V**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **58 kWh**
- Diameter D **36 (max) mm**
- Overall Length C **156 (max) mm**
- Full product code **928151900028**
- Full product name **MASTER SON-T PIA Plus 50W/220 E27 1SL**
- Order code **928151900028**
- Order product name **MST SON-T PIA Plus 50W/220 E27 1SL/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500193094**
- Bar code on pack - EAN1 **8711500192653**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928151900028**
- Net weight per piece **0.047 kg**
- Bulb Finish **Clear**
- System Description **External Ignitor**
- Lamp Wattage **50 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **25 (max) Ra8**
- ILCOS code **ST-50-H/S-E27**
- Cap-Base Temperature **200 (max) C**
- Bulb Temperature **350 (max) C**
- Life to 50% failures **30000 hr**
- Light Center Length L **104 mm**
- Mercury (Hg) Content **12 mg**
- Chromaticity Coordinate X **540 -**
- Chromaticity Coordinate Y **420 -**
- LLMF EM 2000h Rated **92 %**

- Lum Efficacy Rated EM 25°C **81 Lm/W**
- Luminous Flux EM 25°C, Rated **4400 Lm**
- LLMF EM 4000h Rated **90 %**
- LLMF EM 6000h Rated **89 %**
- LLMF EM 8000h Rated **88 %**
- Lamp Wattage EM 25°C, Nominal **50.0 W**
- Lamp Wattage EM 25°C, Rated **53.0 W**
- LLMF EM 12000h Rated **87 %**
- LLMF EM 16000h Rated **86 %**
- LLMF EM 20000h Rated **86 %**
- Lamp Voltage **91 V**
- Lamp Current EM **0.75 A**
- Luminance Average EM **310 cd/cm²**
- Life to 20% failures **22000 hr**
- Life to 5% failures **14000 hr**
- Arc Length O **35 mm**
- Ignition Time **5 (max) s**
- Run-up time 90% **4 (max) min**
- LSF EM 2000h Rated, 12h cycle **99 %**
- LSF EM 4000h Rated, 12h cycle **99 %**
- LSF EM 6000h Rated, 12h cycle **99 %**
- LSF EM 8000h Rated, 12h cycle **99 %**
- LSF EM 12000h Rated, 12h cycle **96 %**
- LSF EM 16000h Rated, 12h cycle **92 %**
- LSF EM 20000h Rated, 12h cycle **83 %**
- Re-ignition Time [sec] **30 (max) s**
- Life to 10% failures **17000 hr**
- Ratio scotopic/photopic lumens **0.50 -**

High Pressure Sodium lamp with clear tubular outer bulb, high output and long reliable lifetime





