

MASTER SOX-E 18W BY22d 1SL/12

Kod produktu: 58090



Dane techniczne:

- Cap-Base **BY22d**
- Bulb **T50 [T 50mm]**
- Color Temperature **1800 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **19 kWh**
- Diameter D **52 (max) mm**
- Overall Length C **216 (max) mm**
- Full product code **928145200008**
- Full product name **MASTER SOX-E 18W BY22d 1SL**
- Order code **928145200008**
- Order product name **MASTER SOX-E 18W BY22d 1SL/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500193407**
- Bar code on pack - EAN1 **8711500192806**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928145200008**
- Net weight per piece **0.150 kg**
- Lamp Wattage **18 W**
- Operating Position **h110 [Hanging +/-110D or Base Up (BU)]**
- ILCOS code **LSE-E18-BY22d**
- Cap-Base Temperature **150 (max) C**
- Bulb Temperature **150 (max) C**
- Life to 50% failures **18000 hr**
- Mercury (Hg) Content **0 mg**
- Lumen Maintenance 2000h **95 %**
- Lumen Maintenance 5000h **90 %**
- Luminous Efficacy Lamp EM **100 Lm/W**
- Luminous Flux Lamp EM **1800 Lm**
- Lamp Wattage EM **18.0 W**
- Lamp Voltage **57 V**
- Lamp Current EM **0.33 A**
- Luminance Average EM **7 cd/cm2**
- Life to 20% failures **12000 hr**
- Life to 5% failures **6000 hr**

Low Pressure Sodium lamp with improved efficacy

Low Pressure Sodium lamp with improved efficacy

Features

Uniform sodium distribution in the discharge tube by means of dimples for a more stable discharge, higher efficacy and better lumen maintenance and lamp life

Special coating of SOX-E outer tube results in higher lamp efficacy than SOX

Monochromatic yellow color with non-existent color rendering

Applications

Road lighting, railway marshalling yards and crossings, airports, harbours and docks, quarries, foundries and rolling mills

Security and orientation lighting



