SOX 55W BY22d 1SL/12

Kod produktu: 58097



Dane techniczne:

- Bulb **T15 [Diameter: 1.97 inch]**
- Color Temperature **1800 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A++**
- Energy consumption kWh/1000h **61 kWh**
- Diameter D **52 (max) mm**
- Overall Length C **425 (max) mm**
- Full product code **928146000028**
- Full product name **SOX 55W BY22d 1SL**
- Order code **928146000028**
- Order product name **SOX 55W BY22d 1SL**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500600141**
- Bar code on pack - EAN1 **8711500179753**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928146000028**
- Net weight per piece **0.300 kg**
- Operating Position **Base Up +/- 110 D [Hanging +/-110D or Base Up (BU)]**
- ILCOS code **LS-55-BY22d**
- Cap-Base Temperature **150 (max) C**
- Lamp Current **0.51 A**
- Bulb Temperature **150 (max) C**
- Base **DC Bayonet**
- RatedAvgLife(See Family Notes) **18000 hr**
- Mercury (Hg) Content **0 mg**
- Initial Lumens **7800 Lm**
- Lumen Maintenance 2000h **102 %**
- Lumen Maintenance 5000h **100 %**
- Luminous Efficacy Lamp EM **140 Lm/W**
- Lamp Wattage EM **56.0 W**
- Lamp Voltage **109 V**
- Luminance Average EM **9 cd/cm2**
- Life to 20% failures **12000 hr**
- Life to 5% failures **6000 hr**
- Energy Used **55 W**

High energy efficiency low pressure sodium lamps for indoor and outdoor applications.

Low Pressure Sodium lamp


biuro@elektriko.pl +48 737 449 514

Features


Uniform sodium distribution in the discharge tube by means of dimples for a more stable discharge, higher efficacy and better lumen maintenance and lamp life
Monochromatic yellow color with non-existent color rendering

Applications


Road lighting, railway marshalling yards and crossings, airports, harbours and docks, quarries, foundries and rolling mills
Security and orientation lighting











biuro@elektriko.pl +48 737 449 514











biuro@elektriko.pl
+48 737 449 514