

SOX 90W BY22d 1SL/12

Kod produktu: 58098



Dane techniczne:

- Cap-Base **BY22d**
- Bulb **T65 [T 65mm]**
- Color Temperature **1800 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A++**
- Energy consumption kWh/1000h **100 kWh**
- Diameter D **66 (max) mm**
- Overall Length C **528 (max) mm**
- Full product code **928146500008**
- Full product name **SOX 90W BY22d 1SL**
- Order code **928146500008**
- Order product name **SOX 90W BY22d 1SL/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500182753**
- Bar code on pack - EAN1 **8711500179777**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928146500008**
- Net weight per piece **0.483 kg**
- Lamp Wattage **90 W**
- Operating Position **p20 [Parallel +/-20D or Horizontal(HOR)]**
- ILCOS code **LS-90-BY22d-/H**
- Cap-Base Temperature **150 (max) C**
- Lamp Current **0.82 A**
- Bulb Temperature **150 (max) C**
- Life to 50% failures **18000 hr**
- Mercury (Hg) Content **0 mg**
- Lumen Maintenance 2000h **95 %**
- Lumen Maintenance 5000h **90 %**
- Luminous Efficacy Lamp EM **150 Lm/W**
- Luminous Flux Lamp EM **13600 Lm**
- Lamp Wattage EM **91.0 W**
- Lamp Voltage **112 V**
- Luminance Average EM **9 cd/cm2**
- Life to 20% failures **12000 hr**
- Life to 5% failures **6000 hr**

Low Pressure Sodium lamp

Low Pressure Sodium lamp

Features

Uniform sodium distribution in the discharge tube by means of dimples for a more stable discharge, higher efficacy and better lumen maintenance and lamp life

Monochromatic yellow color with non-existent color rendering

Applications

Road lighting, railway marshalling yards and crossings, airports, harbours and docks, quarries, foundries and rolling mills

Security and orientation lighting



