

MHN-TD 70W/842 RX7s 1CT/12

Kod produktu: 58109



Dane techniczne:

- Cap-Base **RX7s**
- Bulb **TD**
- Color Code **842 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **82 kWh**
- Diameter D **19.5 (max) mm**
- Overall Length C **117.6 (max) mm**
- Full product code **928070205190**
- Full product name **MHN-TD 70W/842 RX7s 1CT**
- Order code **928070205190**
- Order product name **MHN-TD 70W/842 RX7s 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291215332**
- Bar code on pack - EAN1 **8718291215325**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928070205190**
- Net weight per piece **0.028 kg**
- Bulb Finish **Clear**
- Cap-Base Information **na**
- Lamp Wattage **70 W**
- Operating Position **p45 [Parallel +/-45D or Horizontal(HOR)]**
- Color Rendering Index **80 Ra8**
- ILCOS code **MD/UB-70/842-H-RX7s-22/117.6**
- Bulb Temperature **500 (max) C**
- Pinch Temperature **280 (max) C**
- Life to 50% failures **10500 hr**
- Light Center Length L **57.0 mm**
- Mercury (Hg) Content **11 mg**
- Insertion Length B **114.2 (max) mm**
- Lumen Maintenance 2000h **85 %**
- Chromaticity Coordinate X **370 -**

- Chromaticity Coordinate Y **370 -**
- Lumen Maintenance 5000h **80 %**
- Lamp Wattage EM 25°C, Nominal **70.0 W**
- Lamp Wattage EM 25°C, Rated **75.0 W**
- Luminous Efficacy Lamp EM **76 Lm/W**
- Luminous Flux Lamp EM **5700 Lm**
- Lamp Voltage **90 V**
- Lamp Current EM **1.0 A**
- Lumen Maintenance 10000h **75 %**
- Luminance Average EM **1500 cd/cm2**
- Life to 20% failures **8000 hr**
- Life to 5% failures **5000 hr**
- Arc Length O **7.7 mm**
- Diameter D [inch] **0.75 in**
- Light Center Length L [inch] **2.24 in**
- Overall Length C [inch] **4.63 (max) in**
- Footnotes HID **392 [Supply volts must be +/- 5% of rated ballast line volts for reactor type and +/- 10% for CWA or electronic ballasts.]**
- Ignition Peak Voltage **1800 (min) V**

Double-ended quartz Metal-halide lamp

Double-ended quartz Metal-halide lamp

Features

Quartz discharge tube containing high-pressure mercury and a mixture of dysprosium, holmium and thulium halides (4200 K) or tin iodide (3000 K), with sodium and thallium added for color correction and arc stabilization

Double-ended lamps housed in a tubular clear UV-Block quartz evacuated outer envelope

Restricted burning position

Applications

Indoors - accent lighting, general lighting in downlighters, e.g. in shops and malls

Downlighters, uplighters and wall-washers, e.g. in shops and malls

Outdoors - floodlighting monuments, facades and billboards





