

MASTERC CDM-T 150W/942 G12 1CT

Kod produktu: 58115



Dane techniczne:

- Cap-Base **G12**
- Bulb **T19 [T 19mm]**
- Color Code **942 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **165 kWh**
- Diameter D **20 (max) mm**
- Overall Length C **110 (max) mm**
- Full product code **928084605131**
- Full product name **MASTERC colour CDM-T 150W/942 G12 1CT**
- Order code **928084605131**
- Order product name **MASTERC CDM-T 150W/942 G12 1CT**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500200068**
- Bar code on pack - EAN1 **8711500200051**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928084605131**
- Net weight per piece **0.033 kg**
- Bulb Finish **Clear**
- Lamp Wattage **150 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **96 Ra8**
- ILCOS code **MT/UB-150/942-H-G12-21/100**
- Cap-Base Temperature **280 (max) C**
- Bulb Temperature **650 (max) C**
- Pinch Temperature **350 (max) C**
- Color Temperature Technical **4050 K**
- Light Center Length L **55 (min), 56 (nom), 57 (max) mm**
- Mercury (Hg) Content **10.4 mg**
- Chromaticity Coordinate X **0.375 -**
- Chromaticity Coordinate Y **0.363 -**
- Lamp Wattage EM 25°C, Nominal **150.0 W**

- Lamp Wattage EM 25°C, Rated **145.0 W**
- Lamp Wattage EL 25°C, Rated **150.0 W**
- Lamp Wattage EL 25°C, Nominal **150.0 W**
- Luminous Efficacy Lamp EM **83 Lm/W**
- Luminous Flux Lamp EM **12000 Lm**
- Lamp Voltage **90 V**
- Lamp Current EM **1.9 A**
- Damage Factor D/fc **0.4 (max)** -
- Arc Length O **8 mm**
- Luminous Efficacy Lamp EL **85 Lm/W**
- Luminous Flux Lamp EL **12700 Lm**
- System Power EL **167 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **1.7 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Reference Length A **96 (max) mm**
- Diameter D [inch] **0.75 in**
- Light Center Length L [inch] **2.21875 in**
- Overall Length C [inch] **4.34375 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **11000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **12000 hr**
- Lumen Maintenance EL 2000h **85 %**
- Design Mean Lumens EL **10800 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Ignition Peak Voltage **3500 (min) V**
- System Power EM **165 W**
- Life to 5% failures EM **9000 hr**
- Life to 20% failures EM **11000 hr**
- Lumen Maintenance EM 2000h **85 %**
- Lumen Maintenance EL 5000h **80 %**
- Lumen Maintenance EM 5000h **75 %**
- Design Mean Lumens EM **9900 Lm**
- Lumen Maintenance EL 10000h **70 %**
- Lumen Maintenance EM 10000h **65 %**

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light





