

# MASTERC CDM-TC 20W/830 G8.5 1CT/12

Kod produktu: 58121



## Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14** [T 14 mm]
- Color Code **830** [CCT of 3000K]
- Color Designation (text) **Warm White**
- Color Temperature **2980 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **22 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928183405125**
- Full product name **MASTERCcolour CDM-TC 20W/830 G8.5 1CT**
- Order code **928183405125**
- Order product name **MASTERC CDM-TC 20W/830 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900871593**
- Bar code on pack - EAN1 **8727900871586**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928183405125**
- Net weight per piece **9.000 gr**
- Bulb Finish **Clear**
- Lamp Wattage **20 W**
- Operating Position **any** [Any or Universal (U)]
- Color Rendering Index **85 Ra8**
- ILCOS code **MT/UB-20/830-H-G8.5-17/85**
- Bulb Material **UV-Block Quartz**
- Bulb Temperature **320 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **2980 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **3.5 mg**
- Chromaticity Coordinate X **0.434 -**
- Chromaticity Coordinate Y **0.391 -**
- Lamp Wattage EL 25°C, Rated **20.0 W**

- Lamp Wattage EL 25°C, Nominal **20.0 W**
- Lamp Voltage **94 V**
- Damage Factor D/fc **0.4 (max) -**
- Arc Length O **4 mm**
- Luminous Efficacy Lamp EL **90 Lm/W**
- Luminous Flux Lamp EL **1800 Lm**
- System Power EL **23.5 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.215 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.55 in**
- Overall Length C [inch] **3.346 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **12000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **15000 hr**
- Lumen Maintenance EL 2000h **87 %**
- Design Mean Lumens EL **1400 Lm**
- Lumen Maintenance EL 12000h **77 %**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance EL 5000h **83 %**
- Lumen Maintenance EL 10000h **78 %**

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light



