

MASTERC CDM-TC 35W/842 G8.5 1CT/12

Kod produktu: 58123



Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14 [T 14 mm]**
- Color Code **842 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **41 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928093805125**
- Full product name **MASTERCcolour CDM-TC 35W/842 G8.5 1CT**
- Order code **928093805125**
- Order product name **MASTERC CDM-TC 35W/842 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500209580**
- Bar code on pack - EAN1 **8711500209573**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928093805125**
- Net weight per piece **10.000 gr**
- Bulb Finish **Clear**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **85 Ra8**
- ILCOS code **MT/UB-35/842-H-G8.5-17/85**
- Bulb Material **UV-Block Quartz**
- Bulb Temperature **500 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **4200 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **2.7 mg**
- Chromaticity Coordinate X **0.374 -**
- Chromaticity Coordinate Y **0.369 -**
- Lamp Wattage EL 25°C, Rated **39.0 W**

- Lamp Wattage EL 25°C, Nominal **35.0 W**
- Lamp Voltage **85 V**
- Damage Factor D/fc **0.5 (max) -**
- Arc Length O **5 mm**
- Luminous Efficacy Lamp EL **79 Lm/W**
- Luminous Flux Lamp EL **3100 Lm**
- System Power EL **44 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.46 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.5 in**
- Light Center Length L [inch] **2 in**
- Overall Length C [inch] **3.34375 (max) in**
- Life to 10% failures EL **8000 hr**
- Life to 20% failures EL **9000 hr**
- Life to 5% failures EL **6000 hr**
- Life to 50% failures EL **12000 hr**
- Lumen Maintenance EL 2000h **85 %**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance EL 5000h **80 %**
- Lumen Maintenance EL 10000h **70 %**

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light



