

MASTERC CDM-TC 70W/830 G8.5 1CT/12

Kod produktu: 58124



Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14 [T 14 mm]**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **80 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928086505131**
- Full product name **MASTERCcolour CDM-TC 70W/830 G8.5 1CT**
- Order code **928086505131**
- Order product name **MASTERC CDM-TC 70W/830 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500201683**
- Bar code on pack - EAN1 **8711500201676**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928086505131**
- Net weight per piece **0.010 kg**
- Bulb Finish **Clear**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **83 Ra8**
- ILCOS code **MT/UB-70/830-H-G8.5-17/85**
- Bulb Material **UV-Block Quartz**
- Bulb Temperature **550 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **2915 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **4.5 mg**
- Chromaticity Coordinate X **0.439 -**
- Chromaticity Coordinate Y **0.398 -**
- Lamp Wattage EL 25°C, Rated **73.0 W**

- Lamp Wattage EL 25°C, Nominal **70.0 W**
- Lamp Voltage **83 V**
- Damage Factor D/fc **0.3 (max)** -
- Arc Length O **7 mm**
- Luminous Efficacy Lamp EL **88 Lm/W**
- Luminous Flux Lamp EL **6400 Lm**
- System Power EL **83 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.87 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.5 in**
- Light Center Length L [inch] **2 in**
- Overall Length C [inch] **3.34375 (max) in**
- Life to 10% failures EL **8000 hr**
- Life to 20% failures EL **9000 hr**
- Life to 5% failures EL **6000 hr**
- Life to 50% failures EL **12000 hr**
- Lumen Maintenance EL 2000h **85 %**
- Design Mean Lumens EL **5100 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Ignition Peak Voltage **3500 (min) V**
- Lumen Maintenance EL 5000h **75 %**
- Lumen Maintenance EL 10000h **65 %**

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light





