

MASTERC CDM-TC - 70W/842 G8.5 1CT/12

Kod produktu: 58125



Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14 [T 14 mm]**
- Color Code **842 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **80 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928094605131**
- Full product name **MASTERCcolour CDM-TC - 70W/842 G8.5 1CT**
- Order code **928094605131**
- Order product name **MASTERC CDM-TC - 70W/842 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500212764**
- Bar code on pack - EAN1 **8711500212757**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928094605131**
- Net weight per piece **0.010 kg**
- Bulb Finish **Clear**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **89 Ra8**
- ILCOS code **MT/UB-70/842-H-G8.5-17/85**
- Bulb Material **UV-Block Quartz**
- Bulb Temperature **700 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **4200 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **7 mg**
- Chromaticity Coordinate X **0.362 -**
- Chromaticity Coordinate Y **0.363 -**
- Lamp Wattage EL 25°C, Rated **73.0 W**

- Lamp Wattage EL 25°C, Nominal **70.0 W**
- Lamp Voltage **88 V**
- Damage Factor D/fc **0.5 (max) -**
- Arc Length O **5 mm**
- Luminous Efficacy Lamp EL **79 Lm/W**
- Luminous Flux Lamp EL **5800 Lm**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.830 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Light Center Length L [inch] **2 in**
- Overall Length C [inch] **3.34375 (max) in**
- Life to 10% failures EL **8000 hr**
- Life to 20% failures EL **9000 hr**
- Life to 5% failures EL **6000 hr**
- Life to 50% failures EL **12000 hr**
- Lumen Maintenance EL 2000h **80 %**
- Design Mean Lumens EL **4300 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance EL 5000h **75 %**
- Lumen Maintenance EL 10000h **65 %**

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light



