

MASTERC CDM-TP 150W/830 PGX12-2 1CT/12

Kod produktu: 58131



Dane techniczne:

- Cap-Base **PGX12-2**
- Bulb **T31 [T 31mm]**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **163 kWh**
- Diameter D **32.00 (max) mm**
- Overall Length C **149 (max) mm**
- Full product code **928087009230**
- Full product name **MASTERC colour CDM-TP 150W/830 PGX12-2 1CT**
- Order code **928087009230**
- Order product name **MASTERC CDM-TP 150W/830 PGX12-2 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500201263**
- Bar code on pack - EAN1 **8711500201256**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928087009230**
- Net weight per piece **77.000 gr**
- Bulb Finish **Clear**
- Lamp Wattage **150 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **86 Ra8**
- ILCOS code **MTS/UB-150/830-H-PGX12-2-91/149**
- Cap-Base Temperature **240 (max) C**
- Bulb Temperature **480 (max) C**
- Life to 50% failures **16000 hr**
- Color Temperature Technical **2900 K**
- Light Center Length L **89 (min), 91 (nom), 93 (max) mm**
- Mercury (Hg) Content **15 mg**
- Chromaticity Coordinate X **444 -**
- Chromaticity Coordinate Y **407 -**
- Lamp Wattage EM 25°C, Nominal **150.0 W**

- Lamp Wattage EM 25°C, Rated **149.0 W**
- Luminous Efficacy Lamp EM **86 Lm/W**
- Luminous Flux Lamp EM **12800 Lm**
- Lamp Voltage **98 V**
- Lamp Current EM **1.8 A**
- Damage Factor D/fc **0.3 (max) -**
- Life to 20% failures **13000 hr**
- Life to 5% failures **9000 hr**
- Arc Length O **9 mm**
- System Power EL **170 W**
- Ignition Time **30 (max) s**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Lumen Maintenance EL 2000h **72 %**
- Lumen Maintenance EL 15000h **60 %**
- PET (NIOSH) **8 (min) h500lx**
- System Power EM **165 W**
- Lumen Maintenance EM 2000h **75 %**
- Lumen Maintenance EL 5000h **70 %**
- Lumen Maintenance EM 5000h **65 %**
- Lumen Maintenance EL 10000h **65 %**
- Lumen Maintenance EM 10000h **55 %**
- Lumen Maintenance EM 15000h **50 %**

Range of protected, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light to be used in open luminaires

Range of protected, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light to be used in open luminaires

Features

Crisp white light

Superior color quality

Lamp design is well-suited to be used in luminaires for power-spots (high intensity) and high-bay general lighting

Double UV-Block quartz sleeves and a hard-glass outer bulb

Applications

Shops and shop windows, offices and public buildings

Decorative outdoor: floodlighting and pedestrian areas





