

MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6

Kod produktu: 58145



Dane techniczne:

- Cap-Base **GX8.5**
- Bulb **R111 [R 111mm]**
- Color Code **942 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- LLMF - end nominal lifetime **60 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **80 kWh**
- Switching cycle **1000X**
- Diameter D **111 (max) mm**
- Overall Length C **95 (max) mm**
- Full product code **928098105330**
- Full product name **MASTERC colour CDM-R111 70W/942 GX8.5 40D 1CT**
- Order code **928098105330**
- Order product name **MASTERC CDM-R111 70W/942 GX8.5 40D 1CT**
- Packing configuration **6**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500213969**
- Bar code on pack - EAN1 **8711500213952**
- Packs per outerbox **6**
- Logistic code(s) - 12NC **928098105330**
- Net weight per piece **0.095 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Bulb Finish **Reflector**
- Beam Angle **40 D**
- Luminous Intensity **8000 cd**
- Luminous flux in 90° cone **2800 Lm**
- Beam Description **Flood [Flood]**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **27 (min), 36 (nom), 45 (max) D**
- Color Rendering Index **96 Ra8**
- ILCOS code **MRS/UB-70/942-H-GX8.5-111/88/40**
- Color Temperature Technical **3900 K**
- Mercury (Hg) Content **6.3 mg**
- Chromaticity Coordinate X **0.381 -**

- Chromaticity Coordinate Y **0.370 -**
- Lamp Wattage EL 25°C, Rated **73.0 W**
- Lamp Voltage **92 V**
- Damage Factor D/fc **0.3 (max) -**
- Luminous Flux Lamp EL **2850 Lm**
- System Power EL **83 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.80 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Overall Length C [inch] **3.6 (max) in**
- Life to 10% failures EL **8500 hr**
- Life to 20% failures EL **9500 hr**
- Life to 5% failures EL **7500 hr**
- Life to 50% failures EL **11000 hr**
- PET (NIOSH) **8 (min) h500lx**
- Lamp Wattage EL **70 W**

The MASTERColour CDM-R111 combines the trendy look of the 111 mm aluminium reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

The MASTERColour CDM-R111 combines the trendy look of the 111 mm aluminium reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Features

High lamp efficacy

Long lamp lifetime compared to incandescent and halogen lamps

The ceramic discharge tube is optimally and stable positioned in the reflector

Twist & Lock system

UV-Block burner capsule

Anti-glare cap design

Applications

Accent and decorative lighting: display lighting with sparkling, theatrical effects, even in surroundings with very high background ambient light levels like shop windows

General lighting: in downlighters, a warm and comfortable atmosphere can be created





