

MASTERC CDM-R111 35W/942 GX8.5 24D 1CT

Kod produktu: 58146



Dane techniczne:

- Cap-Base **GX8.5**
- Bulb **R111 [R 111mm]**
- Color Code **942 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- LLMF - end nominal lifetime **65 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **43 kWh**
- Switching cycle **800X**
- Diameter D **111 (max) mm**
- Overall Length C **95 (max) mm**
- Full product code **928096505330**
- Full product name **MASTERC colour CDM-R111 35W/942 GX8.5 24D 1CT**
- Order code **928096505330**
- Order product name **MASTERC CDM-R111 35W/942 GX8.5 24D 1CT**
- Packing configuration **6**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500213884**
- Bar code on pack - EAN1 **8711500213877**
- Packs per outerbox **6**
- Logistic code(s) - 12NC **928096505330**
- Net weight per piece **0.095 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Bulb Finish **Reflector**
- Beam Angle **24 D**
- Luminous Intensity **7500 cd**
- Luminous flux in 90° cone **1300 Lm**
- Beam Description **Narrow Flood**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **18 (min), 23 (nom), 28 (max) D**
- Color Rendering Index **93 Ra8**
- ILCOS code **MRS/UB-35/942-H-GX8.5-111/88/24**
- Color Temperature Technical **4225 K**
- Mercury (Hg) Content **3.0 mg**
- Chromaticity Coordinate X **0.370 -**

- Chromaticity Coordinate Y **0.365** -
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Voltage **86 V**
- Damage Factor D/fc **0.4 (max)** -
- Luminous Flux Lamp EL **1350 Lm**
- System Power EL **44 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.46 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Overall Length C [inch] **3.75 (max) in**
- Life to 10% failures EL **6500 hr**
- Life to 20% failures EL **7000 hr**
- Life to 5% failures EL **6000 hr**
- Life to 50% failures EL **9000 hr**
- PET (NIOSH) **8 (min) h500lx**
- Lamp Wattage EL **35 W**

The MASTERColour CDM-R111 combines the trendy look of the 111 mm aluminium reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

The MASTERColour CDM-R111 combines the trendy look of the 111 mm aluminium reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Features

High lamp efficacy

Long lamp lifetime compared to incandescent and halogen lamps

The ceramic discharge tube is optimally and stable positioned in the reflector

Twist & Lock system

UV-Block burner capsule

Anti-glare cap design

Applications

Accent and decorative lighting: display lighting with sparkling, theatrical effects, even in surroundings with very high background ambient light levels like shop windows

General lighting: in downlighters, a warm and comfortable atmosphere can be created





