

MASTERC CDM-Tm Mini 35W/930 PGJ5 1CT/12

Kod produktu: 58150



Dane techniczne:

- Cap-Base **PGJ5**
- Bulb **T3.5**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **42 kWh**
- Diameter D **11.2 (max) mm**
- Overall Length C **52 (max) mm**
- Full product code **928093905130**
- Full product name **MASTERC colour CDM-Tm Mini 35W/930 PGJ5 1CT**
- Order code **928093905130**
- Order product name **MASTERC CDM-Tm Mini 35W/930 PGJ5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500211507**
- Bar code on pack - EAN1 **8711500211491**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928093905130**
- Net weight per piece **0.006 kg**
- Bulb Finish **Clear**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **88 (min), 91 (nom) Ra8**
- ILCOS code **MT/UB-35/930-H-PGJ5-11.2/52**
- Cap-Base Temperature **250 (max) C**
- Bulb Temperature **480 (max) C**
- Life to 50% failures **12000 hr**
- Color Temperature Technical **2950 K**
- Light Center Length L **22.3 (min), 22.6 (nom), 22.9 (max) mm**
- Mercury (Hg) Content **2.74 mg**
- Lumen Maintenance 2000h **80 %**
- Chromaticity Coordinate X **0.436 -**
- Chromaticity Coordinate Y **0.396 -**

- Lumen Maintenance 5000h **70 %**
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Wattage EL 25°C, Nominal **35.0 W**
- Lamp Voltage **96 V**
- Lumen Maintenance 10000h **60 %**
- Damage Factor D/fc **0.4 (max) -**
- Life to 20% failures **11000 hr**
- Life to 5% failures **9000 hr**
- Arc Length O **4 mm**
- Luminous Efficacy Lamp EL **77 Lm/W**
- Luminous Flux Lamp EL **3000 Lm**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.4 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.44 in**
- Light Center Length L [inch] **0.89 in**
- Overall Length C [inch] **2.05 (max) in**
- Life to 10% failures **10000 hr**
- Design Mean Lumens EL **2150 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance 1000h **85 %**

Mini, single-ended, high-efficiency Ceramic Metal Halide discharge lamp producing crisp white sparkling light

Mini, single-ended, high-efficiency Ceramic Metal Halide discharge lamp producing crisp white sparkling light

Features

Crisp white sparkling light

Excellent color rendering, with extra red

High efficacy

Stable color performance during lifetime

Mini size

Applications

Accent and display lighting in retail

General and decorative indoor lighting

Outdoor area lighting





