

MASTERC CDM-TC Elite 35W/930 G8.5 1CT/12

Kod produktu: 58160



Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14 [T 14 mm]**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **42 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928189105131**
- Full product name **MASTERC colour CDM-TC Elite 35W/930 G8.5 1CT**
- Order code **928189105131**
- Order product name **MASTERC CDM-TC Elite 35W/930 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900911503**
- Bar code on pack - EAN1 **8727900911497**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928189105131**
- Net weight per piece **0.009 kg**
- Bulb Finish **Clear**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **87 (min), 90 (nom) Ra8**
- ILCOS code **MT/UB-35/930-H-G8.5-17/85**
- Bulb Temperature **500 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **2970 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **4.7 mg**
- Chromaticity Coordinate X **0.435 -**
- Chromaticity Coordinate Y **0.396 -**
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Wattage EL 25°C, Nominal **35.0 W**

- Lamp Voltage **85 V**
- Damage Factor D/fc **0.3 (max) -**
- Arc Length O **4.8 mm**
- Luminous Efficacy Lamp EL **102 Lm/W**
- Luminous Flux Lamp EL **4000 Lm**
- System Power EL **43 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.460 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.6 (max) in**
- Light Center Length L [inch] **2 (min), 2.45 (nom), 2.9 (max) in**
- Overall Length C [inch] **3.3 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **12000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **15000 hr**
- Lumen Maintenance EL 2000h **93 %**
- Design Mean Lumens EL **3300 Lm**
- Lumen Maintenance EL 12000h **78 %**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance EL 5000h **88 %**
- Lumen Maintenance EL 10000h **80 %**

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Features

Crisp white sparkling light
Excellent color rendering, with extra red
High efficacy with unparalleled lumen maintenance
Stable color performance over lifetime
UV-blocking glass

Applications

Accent and display lighting in retail
General and decorative indoor lighting
Outdoor area lighting





