

MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Kod produktu: 58164



Dane techniczne:

- Cap-Base **G8.5**
- Bulb **T14 [T 14 mm]**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **80 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **85 (max) mm**
- Full product code **928189505131**
- Full product name **MASTERC colour CDM-TC Elite 70W/930 G8.5 1CT**
- Order code **928189505131**
- Order product name **MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900911541**
- Bar code on pack - EAN1 **8727900911534**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928189505131**
- Net weight per piece **0.010 kg**
- Bulb Finish **Clear**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **87 (min), 90 (nom) Ra8**
- ILCOS code **MT/UB-70/930-H-G8.5-17/85**
- Bulb Temperature **550 (max) C**
- Pinch Temperature **350 (max) C**
- Color Temperature Technical **2970 K**
- Light Center Length L **51 (min), 52 (nom), 53 (max) mm**
- Mercury (Hg) Content **6.6 mg**
- Chromaticity Coordinate X **0.435 -**
- Chromaticity Coordinate Y **0.396 -**
- Lamp Wattage EL 25°C, Rated **73.0 W**
- Lamp Wattage EL 25°C, Nominal **70.0 W**

- Lamp Voltage **85 V**
- Damage Factor D/fc **0.3 (max)** -
- Arc Length O **7.15 mm**
- Luminous Efficacy Lamp EL **105 Lm/W**
- Luminous Flux Lamp EL **7700 Lm**
- System Power EL **83 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.86 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.6 (max) in**
- Light Center Length L [inch] **2 (min), 2.45 (nom), 2.9 (max) in**
- Overall Length C [inch] **3.3 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **12000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **15000 hr**
- Lumen Maintenance EL 2000h **95 %**
- Design Mean Lumens EL **6650 Lm**
- Lumen Maintenance EL 12000h **82 %**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance EL 5000h **88 %**
- Lumen Maintenance EL 10000h **83 %**

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

Features

Crisp white sparkling light

Excellent color rendering, with extra red

High efficacy with unparalleled lumen maintenance

Stable color performance over lifetime

UV-blocking glass

Applications

Accent and display lighting in retail

General and decorative indoor lighting

Outdoor area lighting





