

MC CDM-R Elite 35W/930 E27 PAR30L 30D

Kod produktu: 58168



Dane techniczne:

- Cap-Base **E27**
- Bulb **PAR30L [PAR 3.75 inch/95mm Long]**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **80 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **43 kWh**
- Switching cycle **1350X**
- Diameter D **97 (max) mm**
- Overall Length C **123 (max) mm**
- Full product code **928108200630**
- Full product name **MASTERColour CDM-R Elite 35W/930 E27 PAR30L 30D**
- Order code **928108200630**
- Order product name **MC CDM-R Elite 35W/930 E27 PAR30L 30D**
- Packing configuration **6**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291241959**
- Bar code on pack - EAN1 **8718291241942**
- Packs per outerbox **6**
- Logistic code(s) - 12NC **928108200630**
- Net weight per piece **0.220 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Bulb Finish **Clear**
- Beam Angle **30 D**
- Luminous Intensity **8000 cd**
- Luminous flux in 90° cone **2400 Lm**
- Beam Description **Flood [Flood]**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **30 D**
- Color Rendering Index **88 (min), 91 (nom) Ra8**
- ILCOS code **MRS/UB-35/930-H-E27-95/125/30**
- Cap-Base Temperature **200 (max) C**

- Bulb Temperature **300 (max) C**
- Color Temperature Technical **2950 K**
- Mercury (Hg) Content **4.7 mg**
- Chromaticity Coordinate X **0.437 -**
- Chromaticity Coordinate Y **0.400 -**
- Lamp Wattage EM 25°C, Rated **40.0 W**
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Wattage EM **35 W**
- Lamp Voltage **88 V**
- Lamp Current EM **0.450 A**
- System Power EL **43 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.450 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Overall Length C [inch] **4.84 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **12000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **15000 hr**
- System Power EM **47 W**
- Life to 5% failures EM **5000 hr**
- Life to 20% failures EM **6000 hr**
- Lamp Wattage EL **35 W**
- Forward Luminous Output **2700 Lm**
- Forward Lum Maintenance 2000h **94 %**
- Forward Luminous Efficacy **69 Lm/W**
- Forward Lum Maintenance 4000h **90 %**
- Forward Lum Maintenance 8000h **86 %**
- Forward Lum Maintenance 12000h **82 %**
- Design Mean Lumens **2000 Lm**
- Forward Lum Maintenance 15000h **80 %**

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Features

Crisp white sparkling light
Excellent color rendering, with extra red
High efficacy combined with unparalleled lumen maintenance
Fits in simple open luminaires
UV-blocking front glass

Applications

Accent and display lighting retail
General and decorative indoor lighting



