

MC CDM-R Elite 70W/930 E27 PAR30L 30D

Kod produktu: 58173



Dane techniczne:

- Cap-Base **E27**
- Bulb **PAR30L [PAR 3.75 inch/95mm Long]**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **80 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **80 kWh**
- Switching cycle **1350X**
- Diameter D **97 (max) mm**
- Overall Length C **123 (max) mm**
- Full product code **928109400630**
- Full product name **MASTERColour CDM-R Elite 70W/930 E27 PAR30L 30D**
- Order code **928109400630**
- Order product name **MC CDM-R Elite 70W/930 E27 PAR30L 30D**
- Packing configuration **6**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291241898**
- Bar code on pack - EAN1 **8718291241881**
- Packs per outerbox **6**
- Logistic code(s) - 12NC **928109400630**
- Net weight per piece **0.220 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Bulb Finish **Clear**
- Beam Angle **30 D**
- Luminous Intensity **14000 cd**
- Luminous flux in 90° cone **4500 Lm**
- Beam Description **Flood [Flood]**
- Lamp Wattage **70 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **30 D**
- Color Rendering Index **89 (min), 92 (nom) Ra8**
- ILCOS code **MRS/UB-70/930-H-E27-95/125/30**
- Cap-Base Temperature **200 (max) C**

- Bulb Temperature **300 (max) C**
- Color Temperature Technical **2900 K**
- Mercury (Hg) Content **6.6 mg**
- Chromaticity Coordinate X **0.443 -**
- Chromaticity Coordinate Y **0.402 -**
- Lamp Wattage EL 25°C, Rated **73.0 W**
- Lamp Voltage **86 V**
- System Power EL **80 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.850 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Overall Length C [inch] **4.84 (max) in**
- Life to 10% failures EL **10000 hr**
- Life to 20% failures EL **12000 hr**
- Life to 5% failures EL **9000 hr**
- Life to 50% failures EL **15000 hr**
- Life to 5% failures EM **5500 hr**
- Life to 20% failures EM **8000 hr**
- Lamp Wattage EL **70 W**
- Forward Luminous Output **5100 Lm**
- Forward Lum Maintenance 2000h **94 %**
- Forward Luminous Efficacy **70 Lm/W**
- Forward Lum Maintenance 4000h **90 %**
- Forward Lum Maintenance 8000h **86 %**
- Forward Lum Maintenance 12000h **82 %**
- Design Mean Lumens **3800 Lm**
- Forward Lum Maintenance 15000h **80 %**

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Features

Crisp white sparkling light

Excellent color rendering, with extra red

High efficacy combined with unparalleled lumen maintenance

Fits in simple open luminaires

UV-blocking front glass

Applications

Accent and display lighting retail

General and decorative indoor lighting



