

CDM-Rm Mini 20W/830 GX10 MR16 10D

Kod produktu: 58179



Dane techniczne:

- Cap-Base **GX10**
- Bulb **MR16 [2inch/50mm]**
- Color Code **830 [CCT of 3000K]**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **70 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **20 kWh**
- Switching cycle **1350X**
- Diameter D **50 (nom), 51 (max) mm**
- Overall Length C **62.75 (nom), 65.4 (max) mm**
- Full product code **928191005331**
- Full product name **MASTERColour CDM-Rm Mini 20W/830 GX10 MR16 10D**
- Order code **928191005331**
- Order product name **CDM-Rm Mini 20W/830 GX10 MR16 10D**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291202752**
- Bar code on pack - EAN1 **8718291202745**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928191005331**
- Net weight per piece **0.047 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Beam Angle **10 D**
- Luminous Intensity **13500 cd**
- Luminous flux in 90° cone **950 Lm**
- Lamp Wattage **20 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **7.5 (min), 10 (nom), 12.5 (max) D**
- Color Rendering Index **81 (min), 84 (nom) Ra8**
- Overall Length Rim C1 **60.9 (max) mm**
- ILCOS code **MRS/UB-20/830-H-GX10-51/54.5/10**
- Life to 50% failures **15000 hr**
- Color Temperature Technical **3000 K**
- Mercury (Hg) Content **3.5 mg**

- Chromaticity Coordinate X **0.440 -**
- Chromaticity Coordinate Y **0.400 -**
- Lamp Wattage EL 25°C, Rated **20.0 W**
- Lamp Voltage **93 V**
- Damage Factor D/fc **0.4 (max) -**
- Life to 20% failures **12000 hr**
- Life to 5% failures **9000 hr**
- System Power EL **23.5 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.215 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Reference Length A **59 (max) mm**
- Life to 10% failures **10000 hr**
- Design Mean Lumens EL **850 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Lamp Wattage EL **20 W**
- Forward Luminous Output **945 (min), 1050 (nom) Lm**
- Forward Lum Maintenance 2000h **92 %**
- Forward Luminous Efficacy **53 Lm/W**
- Forward Lum Maintenance 4000h **85 %**
- Forward Lum Maintenance 8000h **78 %**
- Forward Lum Maintenance 12000h **75 %**
- Forward Lum Maintenance 15000h **70 %**
- Reflector Neck Temperature **215 (max) C**

The new Philips MASTERColour CDM-R mini brings trusted MASTERColour quality to 50mm reflector lamps with the superior output and colour stability to create the right atmosphere to match your customers' retail brand and positioning. The easy way to reflect more sparkle.

The new Philips MASTERColour CDM-R mini brings trusted MASTERColour quality to 50mm reflector lamps with the superior output and colour stability to create the right atmosphere to match your customers' retail brand and positioning. The easy way to reflect more sparkle.

Features

Miniaturized 50mm CDM reflector lamp

High beam intensity

Long lamp lifetime compared to halogen lamps

Twist and lock system

Applications

Miniaturized crisp white light system for superior accent and general lighting in shops



