

MASTERC CDM-Tm Mini GU6.5 20W/830 1CT/12

Kod produktu: 58185



Dane techniczne:

- Cap-Base **GU6.5 [GU6.5]**
- Bulb **T-4**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **22 kWh**
- Diameter D **13.3 (max) mm**
- Overall Length C **56.7 (max) mm**
- Full product code **928183505130**
- Full product name **MASTERC colour CDM-Tm Mini GU6.5 20W/830 1CT**
- Order code **928183505130**
- Order product name **MASTERC CDM-Tm Mini GU6.5 20W/830 1CT/12**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900890846**
- Bar code on pack - EAN1 **8727900890839**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928183505130**
- Net weight per piece **0.007 kg**
- Bulb Finish **Clear**
- Lamp Wattage **20 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **81 (min), 84 (nom) Ra8**
- ILCOS code **MT/UB-20/830-H-GU6.5-13.3/52**
- Cap-Base Temperature **250 (max) C**
- Bulb Temperature **380 (max) C**
- Life to 50% failures **15000 hr**
- Color Temperature Technical **2950 K**
- Light Center Length L **29.7 (min), 30 (nom), 30.3 (max) mm**
- Mercury (Hg) Content **3.5 mg**
- Lumen Maintenance 2000h **87 %**
- Chromaticity Coordinate X **0.436 -**
- Chromaticity Coordinate Y **0.396 -**

- Lumen Maintenance 5000h **83 %**
- Lamp Wattage EL 25°C, Rated **20.0 W**
- Lamp Wattage EL 25°C, Nominal **20.0 W**
- Lamp Voltage **94 V**
- Lumen Maintenance 10000h **78 %**
- Lumen Maintenance 15000h **75 %**
- Damage Factor D/fc **0.5 (max) -**
- Life to 20% failures **12000 hr**
- Life to 5% failures **9000 hr**
- Arc Length O **3.5 mm**
- Luminous Efficacy Lamp EL **90 Lm/W**
- Luminous Flux Lamp EL **1800 Lm**
- System Power EL **23.5 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.215 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **0.5 in**
- Light Center Length L [inch] **1.18 in**
- Overall Length C [inch] **2.25 (max) in**
- Life to 10% failures **10000 hr**
- Design Mean Lumens EL **1400 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Lumen Maintenance 1000h **91 %**
- Lumen Maintenance 4000h **84 %**
- Lumen Maintenance 12000h **77 %**
- Lumen Maintenance 8000h **80 %**

Miniature, single-ended ceramic metal halide lamp GU6.5 twist-lock lamp base, according to global IEC standard

Miniature, single-ended ceramic metal halide lamp GU6.5 twist-lock lamp base, according to global IEC standard

Features

Crisp, white sparkling light

Good color rendering for the 20W lamp, excellent color rendering for the 35W lamp

Best-in-class lumen efficacy and unrivalled lumen maintenance

Miniature size allows design of compact luminaires with high beam intensities for mounting close to illuminated object

Easy replacement due to standard robust twist-lock socket

Applications

Accent and display lighting with a sparkling effect

Decorative outdoor floodlighting



