

CDM-Rm Elite Mini 35W/930 GX10 MR16 10D

Kod produktu: 58191



Dane techniczne:

- Cap-Base **GX10**
- Bulb **MR16 [2inch/50mm]**
- Color Code **930 [CCT of 3000K]**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **86 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **43 kWh**
- Switching cycle **1350X**
- Diameter D **50 (nom), 51 (max) mm**
- Overall Length C **62.75 (nom), 65.4 (max) mm**
- Full product code **928194605330**
- Full product name **MASTERCcolour CDM-Rm Elite Mini 35W/930 GX10 MR16 10D**
- Order code **928194605330**
- Order product name **CDM-Rm Elite Mini 35W/930 GX10 MR16 10D**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291162971**
- Bar code on pack - EAN1 **8718291162964**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928194605330**
- Net weight per piece **0.048 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Beam Angle **10 D**
- Luminous Intensity **20000 cd**
- Luminous flux in 90° cone **2150 Lm**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **9 (min), 12 (nom), 15 (max) D**
- Color Rendering Index **90 (min), 91 (nom) Ra8**
- Overall Length Rim C1 **60.9 (max) mm**
- ILCOS code **MRS/UB-35/930-H-GX10-51/54.5/10**
- Life to 50% failures **15000 hr**
- Color Temperature Technical **3000 K**
- Mercury (Hg) Content **4.7 mg**

- Chromaticity Coordinate X **0.439** -
- Chromaticity Coordinate Y **0.403** -
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Voltage **87 V**
- Damage Factor D/fc **0.4 (max)** -
- Life to 20% failures **12000 hr**
- Life to 5% failures **9000 hr**
- System Power EL **43 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.450 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Reference Length A **59 (max) mm**
- Life to 10% failures **10000 hr**
- Design Mean Lumens EL **2200 Lm**
- PET (NIOSH) **8 (min) h500lx**
- Lamp Wattage EL **35 W**
- Forward Luminous Output **2200 (min), 2400 (nom) Lm**
- Forward Lum Maintenance 2000h **95 %**
- Forward Luminous Efficacy **61.5 Lm/W**
- Forward Lum Maintenance 4000h **93 %**
- Forward Lum Maintenance 8000h **90 %**
- Forward Lum Maintenance 12000h **87 %**
- Forward Lum Maintenance 15000h **86 %**
- Reflector Neck Temperature **315 (max) C**

Mini, very high-efficiency Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Mini, very high-efficiency Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Features

Crisp white sparkling light
Excellent color rendering, with extra red
High efficacy with unparalleled lumen maintenance
Mini design fitting in open luminaires
UV-blocking front glass

Applications

Accent and display lighting in retail
General and decorative indoor lighting



