

MASTERC CDM-R111 Elite 35W/930 GX8.5 24D

Kod produktu: 58198



Dane techniczne:

- Cap-Base **GX8.5**
- Bulb **R111 [R 111mm]**
- Color Code **930 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **70 %**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **43 kWh**
- Switching cycle **1050X**
- Diameter D **111 (max) mm**
- Overall Length C **95 (max) mm**
- Full product code **928195405330**
- Full product name **MASTERC colour CDM-R111 Elite 35W/930 GX8.5 24D**
- Order code **928195405330**
- Order product name **MC CDM-R111 Elite 35W/930 GX8.5 24D**
- Packing configuration **6**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291689454**
- Bar code on pack - EAN1 **8718291689447**
- Packs per outerbox **6**
- Logistic code(s) - 12NC **928195405330**
- Net weight per piece **0.096 kg**
- Warm-up Time to 60% Light Outp **120 s**
- Bulb Finish **Reflector**
- Beam Angle **24 D**
- Luminous Intensity **8500 cd**
- Luminous flux in 90° cone **1750 Lm**
- Beam Description **Narrow Flood**
- Lamp Wattage **35 W**
- Operating Position **any [Any or Universal (U)]**
- Beam Angle Technical **18 (min), 23 (nom), 28 (max) D**
- Color Rendering Index **87 (min), 90 (nom) Ra8**
- ILCOS code **MRS/UB-35/930-H-GX8.5-111/88/24**
- Color Temperature Technical **3000 K**
- Mercury (Hg) Content **4.7 mg**
- Chromaticity Coordinate X **0.432 -**

- Chromaticity Coordinate Y **0.392 -**
- Lamp Wattage EM 25°C, Rated **40.0 W**
- Lamp Wattage EL 25°C, Rated **39.0 W**
- Lamp Wattage EM **35 W**
- Lamp Voltage **89 V**
- Lamp Current EM **0.440 A**
- System Power EL **43 W**
- Ignition Time **30 (max) s**
- Lamp Current EL **0.440 A**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Overall Length C [inch] **3.75 (max) in**
- Life to 10% failures EL **9500 hr**
- Life to 20% failures EL **10500 hr**
- Life to 5% failures EL **8000 hr**
- Life to 50% failures EL **12000 hr**
- System Power EM **47 W**
- Life to 5% failures EM **5000 hr**
- Life to 20% failures EM **6000 hr**
- Lamp Wattage EL **35 W**
- Forward Luminous Output **1800 Lm**
- Forward Lum Maintenance 2000h **90 %**
- Forward Luminous Efficacy **46 Lm/W**
- Forward Lum Maintenance 4000h **85 %**
- Forward Lum Maintenance 8000h **80 %**
- Forward Lum Maintenance 12000h **70 %**
- Design Mean Lumens **1500 Lm**

MASTERColour CDM-R111 Elite combines the trendy look of 111 mm aluminum-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

MASTERColour CDM-R111 Elite combines the trendy look of 111 mm aluminum-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Features

High lamp efficacy

Long lamp lifetime compared to incandescent and halogen lamps

The ceramic discharge tube is optimally positioned and stable in the reflector

UV-block burner capsule

Anti-glare cap design

Applications

Accent and decorative lighting: display lighting with sparkling, theatrical effects, even in surroundings with very high background ambient light levels, such as shops windows

General lighting: in downlighters, a warm and comfortable atmosphere can be created

