

HPI-T 2000W/642 E40 380V CRP/4

Kod produktu: 58239



Dane techniczne:

- Cap-Base **E40**
- Bulb **T100 [T 100mm]**
- Color Code **542 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **3800 K**
- Voltage **380 V**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **2150 kWh**
- Diameter D **101.5 (max) mm**
- Overall Length C **430 (max) mm**
- Full product code **928074209228**
- Full product name **HPI-T 2000W/542 E40 380V 1SL**
- Order code **928074209228**
- Order product name **HPI-T 2000W/542 E40 380V 1SL/4**
- Packing configuration **4**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500202369**
- Bar code on pack - EAN1 **8711500202352**
- Packs per outerbox **4**
- Logistic code(s) - 12NC **928074209228**
- Net weight per piece **572.300 gr**
- Bulb Finish **Clear**
- System Description **High Output**
- Lamp Wattage **2000 W**
- Operating Position **p20 [Parallel +/-20D or Horizontal(HOR)]**
- Color Rendering Index **65 Ra8**
- ILCOS code **MT-2000/42/2B-H-E40-/H**
- Cap-Base Temperature **300 (max) C**
- Bulb Temperature **600 (max) C**
- Life to 50% failures **12000 hr**
- Color Temperature Technical **3800 K**
- Light Center Length L **267 mm**
- Mercury (Hg) Content **256 mg**
- Lumen Maintenance 2000h **90 %**

- Chromaticity Coordinate X **387** -
- Chromaticity Coordinate Y **403** -
- Lumen Maintenance 5000h **80 %**
- Lamp Wattage EM 25°C, Nominal **2000.0 W**
- Lamp Wattage EM 25°C, Rated **1955.0 W**
- Luminous Efficacy Lamp EM **107 Lm/W**
- Luminous Flux Lamp EM **210000 Lm**
- Lamp Voltage **232 V**
- Lamp Current EM **9.1 A**
- Lumen Maintenance 10000h **75 %**
- Luminance Average EM **930 cd/cm2**
- Life to 20% failures **8000 hr**
- Life to 5% failures **3000 hr**
- Arc Length O **120 mm**
- Ignition Time **30 (max) s**
- Life to 10% failures **5500 hr**
- Lumen Maintenance 1500h **92 %**

Quartz metal halide lamps with clear outer bulb

Quartz metal halide lamps with clear outer bulb

Features

Clear tubular outer bulb

Unique 3-band technology resulting in high luminous efficacy, both initially and over long lifetime

Renders a natural white color appearance and good color stability

Applications

Sports lighting, floodlighting of buildings and monuments, area lighting e.g. harbours and building sites





