

MASTERC CDM-T 250W/942 G12 1CT/12

Kod produktu: 58243



Dane techniczne:

- Cap-Base **G12**
- Bulb **T25 [T 25mm]**
- Color Code **942 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **271 kWh**
- Diameter D **25 (max) mm**
- Overall Length C **135 (max) mm**
- Full product code **928094205131**
- Full product name **MASTERC colour CDM-T 250W/942 G12 1CT**
- Order code **928094205131**
- Order product name **MASTERC CDM-T 250W/942 G12 1CT**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500211132**
- Bar code on pack - EAN1 **8711500211125**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928094205131**
- Net weight per piece **0.039 kg**
- Bulb Finish **Clear**
- Lamp Wattage **250 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **91 Ra8**
- ILCOS code **MT/UB-250/942-H-G12-25/135**
- Cap-Base Temperature **280 (max) C**
- Bulb Temperature **700 (max) C**
- Pinch Temperature **350 (max) C**
- Color Temperature Technical **4070 K**
- Light Center Length L **71.5 (min), 72.5 (nom), 73.5 (max) mm**
- Mercury (Hg) Content **19.0 mg**
- Chromaticity Coordinate X **0.376 -**
- Chromaticity Coordinate Y **0.368 -**
- Lamp Wattage EM 25°C, Nominal **250.0 W**

- Lamp Wattage EM 25°C, Rated **247.0 W**
- Luminous Efficacy Lamp EM **105 Lm/W**
- Luminous Flux Lamp EM **26000 Lm**
- Lamp Voltage **93 V**
- Lamp Current EM **3.04 A**
- Damage Factor D/fc **0.28 -**
- Arc Length O **12.3 mm**
- System Power EL **271 W**
- Ignition Time **30 (max) s**
- Re-ignition Time [min] **15 (max) min**
- Run-up time 90% **3 (max) min**
- Reference Length A **122 (max) mm**
- Ratio scotopic/photopic lumens **1.75 -**
- Life to 10% failures EL **4500 hr**
- Life to 20% failures EL **5500 hr**
- Life to 5% failures EL **3500 hr**
- Life to 50% failures EL **8000 hr**
- PET (NIOSH) **8 (min) h500lx**
- Ignition Peak Voltage **3500 (min) V**
- System Power EM **271 W**
- Life to 5% failures EM **3500 hr**
- Life to 20% failures EM **5500 hr**
- Lumen Maintenance EM 2000h **98 %**
- Lumen Maintenance EM 5000h **94 %**
- Lumen Maintenance EM 10000h **86 %**

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light





