

CDM-T Elite 315W/942 PGZ18.1CT/12

Kod produktu: 58244



Dane techniczne:

- Cap-Base **PGZ18**
- Bulb **TMW28 [TMW 28mm]**
- Color Code **942 [CCT of 4200K]**
- Color Designation (text) **Cool White**
- Color Temperature **4200 K**
- Energy Efficiency Label (EEL) **A+**
- Energy consumption kWh/1000h **346 kWh**
- Diameter D **28 (nom), 29 (max) mm**
- Overall Length C **186 (nom), 188 (max) mm**
- Full product code **928601164831**
- Full product name **MASTERC colour CDM-TMW Elite 315W/942 1CT**
- Order code **928601164831**
- Order product name **MASTERC CDM-TMW Elite 315W/942 1CT**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8718291548041**
- Bar code on pack - EAN1 **8718291548034**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **928601164831**
- Net weight per piece **124.000 gr**
- Bulb Finish **Clear**
- Lamp Wattage **315 W**
- Operating Position **any [Any or Universal (U)]**
- Color Rendering Index **85 (min), 93 (nom) Ra8**
- ILCOS code **MT-315/42/1A-H-PGZ18**
- Cap-Base Temperature **250 C**
- Bulb Temperature **600 (max) C**
- Pinch Temperature **300 (max) C**
- Color Temperature Technical **4200 K**
- Light Center Length L **88 (min), 90 (nom), 92 (max) mm**
- Mercury (Hg) Content **24 (max) mg**
- Lumen Maintenance 2000h **98 %**
- Chromaticity Coordinate X **0.376 -**
- Chromaticity Coordinate Y **0.371 -**
- Lumen Maintenance 5000h **94 %**

- Lamp Wattage EL 25°C, Rated **315.0 W**
- Lamp Wattage EL 25°C, Nominal **315.0 W**
- Lamp Voltage **100 V**
- Damage Factor D/fc **0.242 -**
- Arc Length O **14 mm**
- Luminous Efficacy Lamp EL **113 Lm/W**
- Luminous Flux Lamp EL **35500 Lm**
- Ignition Time **3 (max) s**
- Lamp Current EL **3.15 A**
- Re-ignition Time [min] **10 (max) min**
- Run-up time 90% **3 (max) min**
- Diameter D [inch] **1.1 in**
- Light Center Length L [inch] **3.54 in**
- Lumen Maintenance 20000h **81 %**
- Life to 10% failures EL **16000 hr**
- Life to 5% failures EL **12500 hr**
- Life to 50% failures EL **30000 hr**
- PET (NIOSH) **49.7 h500lx**
- Lumen Maintenance EL 10000h **86 %**
- Design Mean Lumens **31150 Lm**
- Lumen Maintenance 12000h **82 %**
- Lumen Maintenance 8000h **88 %**
- Lumen Maintenance - 10% life **96 %**
- Lumen Maintenance - 40% life **82 %**
- Lamp Current Run-Up **4.7 A**
- Picogram per Lumen Hour **25 p/LuHr**
- UV A **7.76 mW/cm²**
- UV B **0.01 mW/cm²**
- UV C **0.06 mW/cm²**
- Maximum Overall Length [inch] **7.44 (max) in**

The medium wattage lighting system that gives superior, longer-lasting white light for both indoor and outdoor use





