

S10 4-65W SIN 220-240V WH EUR/12X25CT

Kod produktu: 58342



Dane techniczne:

- Voltage **220-240 V**
- Overall Length C **40.3 (max) mm**
- Full product code **928392220247**
- Full product name **S10 4-65W SIN 220-240V WH EUR**
- Order code **928392220247**
- Order product name **S10 4-65W SIN 220-240V WH EUR/32X25CT**
- Packing configuration **32X25CT**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500903310**
- Bar code on pack - EAN1 **8711500697691**
- Packs per outerbox **800**
- Logistic code(s) - 12NC **928392220247**
- Net weight per piece **6.930 gr**
- Bar code on intermediate packing - EAN2 **8711500697745**
- Cap-Base Information **2P**
- System Description **Single**
- Capacitor **Yes**
- Color of the Housing **White**
- Lamp Wattage **4-65 W**
- Ambient Temperature **-15 (min), 75 (max) C**
- Overall Width E **21.5 (max) mm**
- Pulse Voltage **900 (min) V**
- Non Reclosure Voltage **140 (min) V**

Range of premium-quality glow switch starters for igniting fluorescent lamps with electromagnetic ballast.

Range of premium-quality glow switch starters for igniting fluorescent lamps with electromagnetic ballast.

Features

Redesigned canister top with two installation notches into which the pins of another starter fit perfectly (patented innovation)

Radioactive-free (patented) and lead-free (RoHS-compliant)

Premium reliability with more than 10,000 safe switches

2-pin igniter in plastic (flame-retardant polycarbonate) canister with high-quality radio-interference suppression capacitor

Well-defined preheat and peak voltage ensure proper ignition

Applications

Ignition of fluorescent lamps of all brands with conventional electromagnetic ballasts using TL-D (T8), TL (T12), TL mini and PL-L lamps

S2 starters are suitable for 110/130 V 4-22 W single applications, 220/240 V 4-6-8-15-18-22 W single applications and 220/240 V 4-22 W series applications. It is recommended for 220/240 V 18 W single applications for optimal performance

S10 starters are suitable for 220/240 V 13 4-65 W single applications. It is required for 220/240 V 13 W single applications

