

HID-PV C 50 /S CDM 220-240V 50/60Hz

Kod produktu: 58447



Dane techniczne:

- Line Frequency **50/60 Hz**
- T-case maximum **80 (max) C**
- Full product code **913700664966**
- Full product name **HID-PV C 50 /S CDM 220-240V 50/60Hz**
- Order code **913700664966**
- Order product name **HID-PV C 50 /S CDM 220-240V 50/60Hz**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900933642**
- Bar code on pack - EAN1 **8727900933635**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **913700664966**
- Net weight per piece **0.240 kg**
- Length A1 **109.6 mm**
- CE marking **Yes**
- Height C1 **32.2 mm**
- T-ambient **-20 (min), 55 (max) C**
- Width B1 **74.4 mm**
- Lifetime 90% surv.@Tcaselife **40000 hr**
- Fixing Hole Diameter D1 **4.9 mm**
- Fixing Hole Distance Length A2 **98.5 mm**
- IP Classification **20**
- Inrush current Peak **26 (max) A**
- Earth leakage current **0.25 (max) mA**
- Inrush current Width **0.25 ms**
- T-storage **-25 (min), 80 (max) C**
- Rated Lamptype **CDM**
- Line Voltage **220-240 V**
- Rated Ballast-Lamp Power **50**
- Rated Number of Lamps **1 piece**
- T-case life **80 C**
- Approval marks **ENEC**
- Automatic restart **Yes**
- Housing **/S**
- Mains voltage safety (AC) **-18%/+10%**
- Operating frequency * **0.14 kHz**
- Mains voltage performance (AC) **-10%/+6%**

- Power losses gear **6 W**
- PowerFactor 100% output power **0.95 -**
- Overvoltage protection 320Vac **48 hr**
- Max ballast on MCB(16A type B) **24 x**
- Cable-Cap outputwires mutual **150 pF**
- Hum and Noise level **37 dB(A)**
- Striplength **10.0-11.0 mm**
- Bumps **IEC 68-2-29 Eb**
- Vibrations **IEC 68-2-6 Fc**
- Safety Standard **IEC 61347-2-3**
- Environmental Standard **ISO 14001**
- Quality Standard **ISO 9000:2000**
- Harmonic current emissions **IEC 61000-3-2**
- EMC Immunity **IEC 61547**
- Humidity **IEC 928-13**
- Constant wattage deviation **-3%/+3%**
- Max. cable length Device/Lamp **1.5 m**
- Connector type **Insert**
- Wcs Ballast contacts **0.50-2.50 mm²**
- Suitable for Outdoor use? **No**
- Ignition Voltage **4.0 (max) kV**
- Ignition switch-off time **18 min**
- Active temperature protection **Yes**
- EMI 9 kHz ... 300MHz **CISPR 15 ed 7.2**

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

Features

Minimal lamp power spread

Low gear energy losses

Lamp end-of-life detection

High Tambient and Tcase temperatures

Long lifetime of 40,000 hours

Applications

Accent and decorative lighting for shops, public spaces, lobbies and offices

Suitable for indoor use only



