

HID-PV C 150 /S CDM 220-240V 50/60Hz

Kod produktu: 58450



Dane techniczne:

- Line Frequency **50/60 Hz**
- T-case maximum **85 (max) C**
- Full product code **913700614066**
- Full product name **HID-PV C 150 /S CDM 220-240V 50/60Hz**
- Order code **913700614066**
- Order product name **HID-PV C 150 /S CDM 220-240V 50/60Hz**
- Packing configuration **12**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500910530**
- Bar code on pack - EAN1 **8711500910523**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **913700614066**
- Net weight per piece **0.360 kg**
- Length A1 **135.0 mm**
- CE marking **Yes**
- Height C1 **32.0 mm**
- T-ambient **-20 (min), 60 (max) C**
- Width B1 **75.0 mm**
- Fixing Hole Diameter D1 **4.8 mm**
- Fixing Hole Distance Length A2 **123.5 mm**
- ENEC certificate **No**
- Fixing Hole Distance Width B2 **63.5 mm**
- Inrush current Peak **50 (max) A**
- Earth leakage current **0.35 (max) mA**
- Inrush current Width **.50 ms**
- T-storage **-25 (min), 85 (max) C**
- Rated Lamptype **CDM**
- Line Voltage **220-240 V**
- Rated Ballast-Lamp Power **150**
- Rated Number of Lamps **1 piece**
- T-case life **75 C**
- Automatic restart **Yes**
- Housing **/S**
- Mains voltage safety (AC) **-18%/+10%**
- Operating frequency * **0.14 kHz**
- Mains voltage performance (AC) **-10%/+6%**
- Power losses gear **10 W**
- PowerFactor 100% output power **0.95 -**
- Overvoltage protection 320Vac **48 hr**

- Max ballast on MCB(16A type B) **6 x**
- Cable-Cap outputwires mutual **200 pF**
- Hum and Noise level **Inaudible**
- Striplength **10.0-11.0 mm**
- F-marking **Yes**
- Bumps **IEC 60068-2-29 Eb**
- Vibrations **IEC 60068-2-6 Fc**
- CB Certificate **Yes**
- Constant wattage deviation **-3%/+3%**
- VDE certificate **Yes**
- Max. cable length Device/Lamp **2.0 m**
- Connector type **Insert**
- Wcs Ballast contacts **0.50-2.50 mm²**
- VDE-EMV certificate **Yes**
- Suitable for Outdoor use? **No**
- Ignition Voltage **5.0 (max) kV**
- Ignition switch-off time **20 min**
- Active temperature protection **Yes**
- EMI 9 kHz ... 300MHz **CISPR 15 ed 7.2**

PrimaVision Power gear is designed for optimal performance of 100 and 150 W CDM lamps – ideal where high-intensity light is key.

PrimaVision Power gear is designed for optimal performance of 100 and 150 W CDM lamps – ideal where high-intensity light is key.

Features

Loop Through feature (in independent version)

Low gear energy losses

Lamp end-of-life detection

High Tambient and Tcase temperatures

Long lifetime of 40,000 hours

Applications

100 and 150 W: high-bay area, accent and decorative lighting for shops, public spaces, lobbies and offices

Suitable for indoor use only



