

SI 54 380-415V 50/60Hz

Kod produktu: 58511



Dane techniczne:

- Line Frequency **50/60 Hz**
- T-case maximum **80 (max) C**
- Full product code **913619149966**
- Full product name **SI 54 380-415V 50/60Hz**
- Order code **913619149966**
- Order product name **SI 54 380-415V 50/60Hz**
- Packing configuration **20**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500908339**
- Bar code on pack - EAN1 **8711500915481**
- Packs per outerbox **20**
- Logistic code(s) - 12NC **913619149966**
- Net weight per piece **0.083 kg**
- Length A1 **114.5 mm**
- CE marking **Yes**
- Height C1 **38.0 mm**
- T-ambient **-20 (min), 75 (max) C**
- Width B1 **41.0 mm**
- Fixing Hole Diameter D1 **4.3 mm**
- Fixing Hole Distance Length A2 **95.0 mm**
- ENEC certificate **Yes**
- T-storage **-25 (min), 80 (max) C**
- Rated Lamptype **HPI**
- Line Voltage **380-415 V**
- Rated Ballast-Lamp Power **2000**
- Rated Number of Lamps **1 piece**
- Housing **SNI-115**
- Mains voltage safety (AC) **-10%/+10%**
- Mains voltage performance (AC) **-8%/+6%**
- Power losses gear **1.0 W**
- Striplength **6.0 mm**
- Application code **54**
- Response voltage **330 V**
- Connector type **Screw**
- Wcs Ballast contacts **0.70-2.50 mm²**

- Ignition Voltage **1.5 (max) kV**
- Ignition type **Parallel**
- Number of ignition pulses **1 x**
- Cable-Cap wires device/lamp **120 nF**

HID ignitors for series systems

HID ignitors for series systems

Features

Ignitors equipped with screw terminal blocks as standard

Series ignitor will only work in series circuits

Applications

Outdoor lighting (most popular application: road and tunnel lighting)

