

SND 58 220-240V 50/60Hz

Kod produktu: 58517



Dane techniczne:

- Line Frequency **50/60 Hz**
- T-case maximum **90 (max) C**
- Full product code **913700185166**
- Full product name **SND 58 220-240V 50/60Hz**
- Order code **913700185166**
- Order product name **SND 58 220-240V 50/60Hz**
- Packing configuration **48**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500930699**
- Bar code on pack - EAN1 **8711500930682**
- Packs per outerbox **48**
- Logistic code(s) - 12NC **913700185166**
- Net weight per piece **0.050 kg**
- Length A1 **84.5 mm**
- CE marking **Yes**
- Height C1 **38.5 mm**
- T-ambient **-20 (min), 85 (max) C**
- Width B1 **41.5 mm**
- Fixing Hole Diameter D1 **4.3 mm**
- Fixing Hole Distance Length A2 **65.0 mm**
- ENEC certificate **Yes**
- Rated Lamptype **SON/CDM/MH/HPI/HPA**
- Line Voltage **220-240 V**
- Rated Ballast-Lamp Power **35-600**
- Rated Number of Lamps **1 piece**
- Housing **SNI-85**
- Mains voltage safety (AC) **-10%/+10%**
- Mains voltage performance (AC) **-8%/+6%**
- Power losses gear **1.0 W**
- Application code **58**
- Maximum ignition time **1185 (max) s**
- Response voltage **195 V**
- Connector type **Screw**
- Wcs Ballast contacts **0.70-2.50 mm²**
- Ignition Voltage **2.8 (min), 5.0 (max) kV**

- Ignition type **Semi-Parallel**
- Ignition Attempts **3** -

HID ignitors for series systems

HID ignitors for series systems

Features

Ignitors equipped with screw terminal blocks as standard

Series ignitor will only work in series circuits

Applications

Outdoor lighting (most popular application: road and tunnel lighting)

