

TMS022 1xTL-D18W HFS

Kod produktu: 58742



Dane techniczne:

- Full product code **910402201603**
- Full product name **TMS022 1xTL-D18W HFS**
- Order code **910402201603**
- Order product name **TMS022 1xTL-D18W HFS**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711559118710**
- Bar code on pack - EAN1 **8711559118703**
- Packs per outerbox **12**
- Logistic code(s) - 12NC **910402201603**
- Net weight per piece **0.645 kg**
- Product family code **TMS022 [TMS022]**
- Number of light sources **1 [1 pc]**
- Kombipack **No**
- Lamp family code **TL-D [MASTER TL-D]**
- Lamp power **18 W [18 W]**
- Compensation circuit **No**
- Gear **HFS [HF Standard]**
- Optic type **No**
- Emergency lighting **No**
- Ingress protection code **IP20 [Finger-protected]**
- Input voltage **230-240 V [230 to 240 V]**
- Protection class IEC **CLI [Safety class I]**
- Mech. impact protection code **IK02 [0.2 J standard]**
- CE mark **CE [CE mark]**
- ENEC mark **ENEC [ENEC mark]**
- Flammability mark **F [For mounting on normally flammable surfaces]**
- Glow-wire test **650/5 [Temperature 650 °C, duration 5 s]**
- Ready-to-install **No**
- Country version **No**
- Housing configuration **No**

TMS022 - 1 pc - MASTER TL-D - 18 W - HF Standard

Lineco TMS022 is a functional and economical surface-mounted batten for 1 or 2 TL-D fluorescent lamps. It offers a choice of two optics, for symmetrical and asymmetrical lighting. Installation is quick and tool-less and can be carried out single-handedly. The repositionable contact block enables flexible connection (with cable entry centrally or via the end


caps). A wide range of snap-on attachments is available.

Features

Choice of one or two TL-D fluorescent lamps
Choice of symmetrical or asymmetrical optics
Quick, tool-less installation
Repositionable contact block
Wide range of snap-on attachments


Applications

Retail
Industry




TM9022 1xTL-D18W HFS

1 x 1380 lm



TM9022 1xTL-D18W HFS

1 x 1380 lm



LVN7775000

2012-05-04

