

SGS102 SON-T100W II MR FG SKD 42/60

Kod produktu: 60996



Dane techniczne:

- Full product code **910925703012**
- Full product name **SGS102 SON-T100W II MR FG SKD 42/60**
- Order code **910925703012**
- Order product name **SGS102 SON-T100W II MR FG SKD 42/60**
- Pieces per pack **0**
- Bar code on outerbox - EAN3 **8727900636512**
- Packs per outerbox **1**
- Logistic code(s) - 12NC **910925703012**
- Net weight per piece **6.410 kg**
- Product family code **SGS102 [SGS102]**
- Number of light sources **1 [1 pc]**
- Kombipack **No**
- Lamp family code **SON-T [SON-T]**
- Lamp power **100 W [100 W]**
- Gear **CONV [Conventional]**
- Optic type **MR [Moveable reflector]**
- Optical cover/lens type **FG [Glass flat]**
- Ingress protection code **IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]**
- Input voltage **230-240 V [230 to 240 V]**
- Protection class IEC II **[Safety class II]**
- Mech. impact protection code **IK08 [5 J vandal-protected]**
- Color **GR [Gray]**
- Ignitor **SKD [Digital semi-parallel MK4]**
- CE mark **CE [CE mark]**
- ENEC mark **ENEC [ENEC mark]**
- Standard tilt angle posttop **15 [15°]**
- Light regulation **No**
- Photocell **No**
- Standard tilt angle side entry **15 [15°]**
- Cap-base **E40 [E40]**
- Mounting device **42/60 [Universal for diameter 42-60 mm]**

SGS102 - SON-T - 100 W - Moveable reflector - Glass flat - Universal for diameter 42-60 mm

Malaga is a versatile road-lighting luminaire. It offers modern styling and quality lighting for safe and comfortable driving, and for area illumination, with low investment and maintenance costs. The optical system has been designed to deliver

good beam control and light output. Malaga provides optimal illuminance and good uniformity when the mounting height approximately equals the road width and the mast spacing is approximately 3.5 times the road width. It is suitable for post-top and side-entry mounting; a wall-mounting bracket is also available.

Features

Modern styling

Effective beam control and uniform light distribution

Suitable for post-top and side-entry mounting; wall-mounting bracket also available

Applications

Residential areas

Roads

Car parks

Industry



