PF19 12W 3000K 120° IP20 White

Kod produktu: 62578



Dane techniczne:

- Light source power **1x12W**
- Weight **0.60 kg**
- Beam angle **120°**
- Color **White**
- Degree of protection (IP) **IP20**
- Type of installation **Universal mounting**
- Housing material **Die cast aluminum**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **AC**
- Voltage rating **230 V**
- Light source included **Yes**
- Light source power **12W**
- Luminarie power **12 W**
- Light distribution **DI**
- Light source luminous flux **1500 lm**
- Color temperature **3000K**
- Class of protection **I**
- Energy class **A+**
- CE **Yes**
- ENEC **Yes**

Extremely thin ceiling luminaire, especially designed for LED light sources. Perfect for discrete and elegant interior lighting.

Materials: polyester painted housing with modern heat dissipation system made of die cast aluminum (standard colors: white, silver, black), faceted, metalized and durable reflector made of polycarbon, polycarbonate opal diffuser


Installation: ceiling mounted, wall mounted

Power: 230 V

H	**F**
40	190
H - Height / Depth	

biuro@elektriko.pl +48 737 449 514

F - Outer diameter



biuro@elektriko.pl
+48 737 449 514